EcoTank Pro L15180

DATASHEET / BROCHURE



EcoTank Business+ Pro L15180

Best for demanding businesses that need the lowest cost per page with high-speed A3 colour and maximum uptime.

KEY FEATURES

- **Fast, time-saving print and scan**

  Enjoy print speeds up to 25ipm in both black and colour, and fast scan speeds[4]

- **Fast print and scan speeds**

  High quality print, copy and scan in one machine, plus large paper trays to save you time, and PCL

- **Easy to use front ink tank**

  Wi-Fi, Wi-Fi Direct, Ethernet, free mobile printing and Epson Remote Services apps

- **Compatible with advanced software solutions**

  Seamlessly integrate software solutions into existing IT infrastructure

- **Number 1 ink tank printer brand worldwide***

  Over 100m EcoTank printers sold worldwide*

EPSON®

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Method	PrecisionCore™ Print Head
Ink Technology	DURABrite™ ET
Printing Resolution	4800 x 1200 DPI
PRINT	
Printing Speed ISO/IEC 24734	25 Pages/min Monochrome, 25 Pages/min Colour
For detailed information on printing speeds please visit http://www.epson.eu/testing.	
SCAN	
Scanner Type	Contact image sensor (CIS)
PAPER / MEDIA HANDLING	
Paper Formats	A4 (21.0x29.7 cm), Legal, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, B5, No. 10 (Envelope), DL (Envelope), C6 (Envelope), C4 (Envelope), Letter, Letter Legal, A3 (29.7x42.0 cm), A3+
Duplex	Yes (A4/A3, plain paper)
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.)
Media Handling	ADF 2-sided copy (A4/A3, plain paper), ADF 2-sided fax (A4/A3, plain paper), ADF 2-sided scan (A4/A3, plain paper), Automatic duplex (A4/A3, plain paper)
GENERAL	
Product dimensions	515 mm x 500 mm x 350 mm (Width x Depth x Height)
Noise Level	6.7 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 52 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode
Compatible Operating Systems	iOS 7
Included Software	Epson Scan 2, Epson Status Monitor, Epson Device Admin, EpsonNet Config
WLAN Security	WEP 128 Bit, WEP 64 Bit, WPA PSK (TKIP), WPA2 PSK (AES)
Mobile and Cloud Printing Services	Apple AirPrint, Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Epson Smart Panel App
OTHER FEATURES	
Panel	Type: Colour, Diagonal: 10.9
Memory Cards	n/a
Features	Touchscreen, Direct print from USB
OTHER	

LOGISTICS INFORMATION

EcoTank Pro L15180

WHAT'S IN THE BOX

- 1 full set of ink (Bk – 127ml, cmY – 70ml)
- Power cable
- Installation/safety manual
- Warranty document
- Main unit
- Quick Start Guide

INK COMPATIBILITY

- 112 EcoTank Pigment Black ink bottle
- 112 EcoTank Pigment Cyan ink bottle
- 112 EcoTank Pigment Magenta ink bottle
- 112 EcoTank Pigment Yellow ink bottle
- WF-78xx / ET-58xx / ET-166xx / L65xx / L151xx Maintenance Box

INK YIELD DATA

Included	* 4,500 Pages	* 2,800 Pages
Replacement		

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.

1. Compared to best-selling similarly-featured printers in Middle East & Africa (IDC, Quarterly Hardcopy Peripherals Tracker, Q1 2023 to Q4 2023 shipments, published Q1 2024). Comparison based on the average yield when printing. Cost per page calculated by dividing the relevant bottle/cartridge average selling price as tracked by IDC by the yield. Epson models included: Eco Tank 112 Ink Bottle Series, Eco Tank 110 Ink Bottle Series, Eco Tank 101 Ink Bottle Series, Eco Tank 103 Ink Bottle Series, Eco Tank 664 Ink Bottle Series.
2. Mobile printing solutions require a wireless and/or an Internet connection to the printer. For a list of Epson Connect enabled printers, compatible devices, apps and ways to connect, visit www.epson.com/eme
3. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.
4. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.com/eme

EPSON®