DATASHEET / BROCHURE

Epson EB-L210SF



KEY FEATURES

Scalable, portable FHD display •
ST display for unrestricted view- ”300 ing without reflections

Bright and energy efficient laser •
4,000lm CLO with 3LCD technology for brighter colours at only 201W

Effortless connectivity options •
Auto-on, wired / wireless display with USB 2A output for smart sticks

Simple to use and built to last •
Virtually maintenance free with 5-year, 12,000hr warranty

Document camera compatibility •
Create and record a live, totally immersive lesson or presentation

EB-L210SF

Best for meeting rooms. Short-throw Full HD laser projector with 4,000 .lumens and wireless connectivity

The EB-L210SF’s short throw lens allows close positioning of the projector to the display, ideal for small rooms and reducing the risk of shadows cast onto the display unlike some other brand projectors, EB-L210SF features 3LCD technology, enabling 4,000 lumens for a bright and vibrant display. The experience is immersive and user-friendly. Scalable from 300”, display sizes can be optimised for each room with one product and a fixed cost, and it supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image. With up-to 30,000 hour long-life laser-light source, it produces a large display up-to 300”, clearly visible from all angles and at a distance, and unlike a flat-panel display, the EB-L210SF can be portable, and there is no glass flat panel to create disruptive, reflected blind spots at certain angles. Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room. With USB 2A power output, HDMI streaming sticks can also be connected to open further .possibilities

Epson EB-L210SF

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	تقنية 3LCD غطاء عدسة الكريستال السائل من RGB
LCD Panel	inches with C2 Fine 0.62
IMAGE	
Color Light Output	(Lumens - 2800 Lumens (economy 4000
White Light Output	(Lumens - 2800 Lumens (economy 4000
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	الليزر
Laser Light source	hr Durability High, 30000 hr Durability Eco 20000
Keystone Correction	Manual vertical: 15, Manual horizontal: 15
Colour Video Processing	Bits Color 10
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.61:1 - 0.45
Zoom	Digital, Factor: 1 - 1.35
Lens	بصري
Screen Size	in - 300 in 55
Projection Lens Focus	Manual
Offset	1 : 11
CONNECTIVITY	
Interfaces	USB 2. النوع B (الخدمة فقط) (1 x), منفذ USB 2. من الفئة B (1 x), توجيه Wi-Fi (1 x), مدخل ميكروفون (1 x), مخرج VGA (1 x)), شبكة محلية لاسلكية (WiFi 5 (1 x) (LAN IEEE 802.11a/b/g/n/ac), مدخل VGA (2 x), واجهة اتصال Ethernet (1 x), Miracast (1 x), RS-232C (Base-T/ 1-Base TX/ 1-Base-T) (1 x), مدخل HDMI (2 x), مخرج صوت بمقبس استريو صغير (1 x), مدخل صوت بمقبس استريو صغير (2 x)
Epson iProjection App	بنية تحتية/مخصصة لأغراض معينة
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	حماية كينسينغتون, إغلاق لوحة التحكم, حماية كلمة المرور, Padlock, فتحة كابل الحماية, قفل وحدة LAN لاسلكية, أمان شبكة LAN لاسلكية, حماية كلمة المرور
Other Features	تصحيح محاذاة الانحناء , تشغيل تلقائي, البحث التلقائي عن المصدر, سماعات مدمجة, متوافق مع CEC, زوم رقمي, التشغيل/إيقاف التشغيل المباشر, كاميرا الوثائق المتوافقة, دمج للحواف, الإعداد المسبق السهل المعروض على الشاشة, Email notification, الشاشة الرئيسية, تصحيح انحراف أفقي ورأسي, فتح/غلق فوري, Mail notification function, مدخل ميكروفون, إدارة الشبكة, عمر طويل لمصدر الضوء, وظيفة النسخ المعروضة على الشاشة, تقنية كويك كورنر, عرض ضوئي عبر الشبكة, وظيفة تقسيم الشاشة, معالج الإعداد, مطابقة الشاشة, تحكم عبر الويب, التحكم عن بُعد عبر الويب, إمكانية توصيل بشبكة LAN لاسلكية, تطبيق iProjection
Video Colour Modes	سبورة سوداء, حركي, عرض تقديمي, sRGB, DICOM SIM, سينما, Multi Projection
Projector Control	AMX, Crestron (الشبكة), Extron, Crestron (منفذ RS-232c فقط), Crestron Integrated Partner, Extron IP Link, Crestron RoomView, اكتشاف جهاز AMX, Extron XTP, بروتوكول Control4 Simple Device Discovery.

EPSON®

Epson EB-L210SF

WHAT'S IN THE BOX

- كابل للكهرباء
- التحكم عن بعد مع بطاريات
- كبل HDMI بطول 1.8 متر
- دليل التشغيل السريع
- مستندات الضمان

</ "١٣٥١٠٧"=STEPTABLE TT>

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	(W, 144 W (economy), 0.5 W (standby 201
Product dimensions	(mm x 337 mm x 90 mm (Width x Depth x Height 325
Heat Dissipation	BTUperhour 884
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Management, Epson Projector Content Manager, EasyMP Multi PC Projection
Noise Level	(Normal: 37 dB (A) - Economy: 27 dB (A
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	% Operation 20 % - 80 %, Storage 10 % - 90
Options	صندوق تحكم واتصالات, كاميرا جهاز العرض الضوئي, حامل التركيب على الحائط, حامل سقفي, السماعة الخارجية
Loudspeaker	W 16
Room Type / Application	غرفة اجتماعات / قاعة دراسية, غرفة اجتماعات
Positioning	تركيب في السقف, تركيب على الحائط, تثبيت على الطاولة
Colour	White
OTHER	

EPSON®