

Epson EB-L260F

DATASHEET / BROCHURE



EB-L260F

Best for meeting rooms and presentations. Full HD 4,600-lumen laser projector with wireless connectivity and scalable display.

The perfect Full HD laser display solution allows you to upgrade to laser performance and reliability without paying a premium. High contrast of 2,500,000:1 and 3LCD technology ensures professional, outstanding and clear content delivery in any working environment while keeping audiences engaged. Offers MTR auto power-on function by HDMI video signal detection and an array of connectivity options including Dual HDMI and built-in wireless LAN to stream content from laptops or mobile devices with Screen Mirroring (Miracast) - PIN code support and display dialog username when connected. Miracast to projector allows teacher to block student interruption while teacher is projecting. USB power supply (2A) for easy smart stick connection. Compatible with iProjection software for easy connectivity with mobile devices and content sharing. Project for longer with exceptional reliability and a longer usage life of up to 30,000 hours in Eco Mode (20,000 hours normal). The EB-L260F is covered by a five-year warranty. This light weight and compact projector supports 360 degree installation without compromising the display quality and supports 16:6 ultra-widescreen, HDMI output and edge blending for multi-projector installs.

KEY FEATURES

- **4,600 lumens brightness display**
Full HD crisp images and bright colours, even in well-lit rooms
- **A scalable display**
Flexible scalable display from 31 inches up to 310 inches
- **Stream content easily**
Wireless, MTR auto power-on by HDMI and easy smart stick connection.
- **Fit and forget reliability**
Easy installation with multi-projection and signage function.
- **The complete solution**
With an incredible contrast ratio of 5,000,000:1, the EB-L260F delivers vivid, lifelike content and defined shadow detail with deeper blacks

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-L260F

TECHNOLOGY

| | |
|-------------------|---|
| Projection System | 3LCD Technology RGB liquid crystal shutter |
| LCD Panel | 0.62 inches with C2 Fine |

IMAGE

| | |
|-------------------------|---|
| Color Light Output | 4600 Lumens - 3200 Lumens (economy) |
| White Light Output | 4600 Lumens - 3200 Lumens (economy) |
| Resolution | 1080p |
| High Definition | Full HD |
| Contrast Ratio | 5,000,000 |
| Light Source | Laser |
| Laser Light source | 20000 hr Durability High, 30000 hr Durability Eco |
| Keystone Correction | Manual vertical: 30, Manual horizontal: 30 |
| Colour Video Processing | 10 Bits Color |
| Colour Reproduction | Upto 1.07 billion colours |

OPTICAL

| | |
|------------------------------|---------------------------|
| Throw Ratio | 1.32 - 2.12:1 |
| Zoom | Digital, Factor: 1 - 1.62 |
| Lens | Optical |
| Screen Size | 31 in - 310 in |
| Projection Lens F Number | 1.77 |
| Projection Lens Focal Length | 29.1 mm |
| Projection Lens Focus | Manual |
| Offset | 10 : 1 |

CONNECTIVITY

| | |
|-----------------------|---|
| Interfaces | Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0-A (1 x), Jack plug out (1 x), VGA out (1 x), Microphone input (1 x), Cinch audio out (1 x), Wi-Fi Direct (1 x), Jack plug in (2 x), Miracast (1 x), RS-232C (1 x), VGA in (2 x), USB 2.0 (1 x), HDMI (HDCP 2.2) (2 x), Composite in (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x) |
| Epson iProjection App | Ad-Hoc / Infrastructure |
| Network Protocol | PJLink, HTTPS, IPv6, SNMP, ESC/VP.net |

ADVANCED FEATURES

| | |
|--------------------|--|
| Security | Kensington lock, Security cable hole, Wireless LAN unit lock, Padlock, Security bar, Control panel lock, Password protection, Wireless LAN security |
| Other Features | AV Mute Slide, Auto source search, Built-in speaker, Customizable user logo, Document Camera Compatible, Home Screen, Long light source life, OSD copy function, PC Free, Quick Corner, Screen share, Screen Mirroring, Split-Screen-Function, Wireless LAN capable, iProjection App, Arc Correction, Auto Power On, Direct Power on/off, Edge Blending, Horizontal and vertical keystone correction, Schedule Function, Super resolution, Web Control, CEC compatible |
| Video Colour Modes | Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Blackboard, Multi Projection |
| Projector Control | Extron IP Link, Control4 Simple Device Discovery Protocol, AMX Device Discovery, Crestron Integrated Partner |

EPSON[®]

PRODUCT SPECIFICATIONS

| GENERAL | |
|-------------------------|---|
| Power consumption | 199 W, 260 W (economy), 144 W (standby) |
| Heat Dissipation | 884 BTUperhour |
| Product dimensions | 325 mm x 299 mm x 90 mm (Width x Depth x Height) |
| Supply Voltage | AC 220 V - 240 V, 50 Hz - 60 Hz |
| Included Software | EasyMP Multi PC Projection, Epson Projector Management, Epson Creative Projection, Epson Projector Content Manager |
| Noise Level | Normal: 37 dB (A) - Economy: 27 dB (A) |
| Supported Temperature | Storage -10 °C - 60 °C |
| Supported Humidity | Operation 20 % - 80 %, Storage 10 % - 90 % |
| Options | Wall mount |
| Loudspeaker | 16 W |
| Room Type / Application | Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction |
| Positioning | Desktop, Ceiling Mounted, Floor, Wall Mounted |
| Colour | White |

OTHER

Epson EB-L260F

WHAT'S IN THE BOX

- Remote control incl. batteries
- Power cable
- Main unit
- HDMI Cable
- Warranty card
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series V13H134A60
- Ceiling mount / Floor stand - ELPMB60B V12H963110
- Ceiling mount / Floor stand - ELPMB60W V12H963210
- Ceiling pipe - ELPFP13 - 668-918mm V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm V12H003P14
- Control and Connection Box - ELPCB03

- Control and Connection Box - ELPCB03 [240v] V12H927040DA
- Control and Connection Box - ELPCB03N V12HB11040
- External Speaker - ELPSP02 V12H467040
- External Speaker - ELPSP02 - [240v] V12H467040DA