



EB-L260F

Best for meeting rooms and presentations. Full HD 4,600-lumen laser projector with wireless connectivity and scalable display.

The perfect Full HD laser display solution allows you to upgrade to laser performance and reliability without paying a premium. High contrast of 2,500,000:1 and 3LCD technology ensures professional, outstanding and clear content delivery in any working environment while keeping audiences engaged. Offers MTR auto power-on function by HDMI video signal detection and an array of connectivity options including Dual HDMI and built-in wireless LAN to stream content from laptops or mobile devices with Screen Mirroring (Miracast) - PIN code support and display dialog username when connected. Miracast to projector allows teacher to block student interruption while teacher is projecting. USB power supply (2A) for easy smart stick connection. Compatible with iProjection software for easy connectivity with mobile devices and content sharing. Project for longer with exceptional reliability and a longer usage life of up to 30,000 hours in Eco Mode (20,000 hours normal). The EB-L260F is covered by a five-year warranty. This light weight and compact projector supports 360 degree installation without compromising the display quality and supports 16:6 ultra-widescreen, HDMI output and edge blending for multi-projector installs.

KEY FEATURES

- **4,600 lumens brightness display**
Full HD crisp images and bright colours, even in well-lit rooms
- **A scalable display**
Flexible scalable display from 31 inches up to 310 inches
- **Stream content easily**
Wireless, MTR auto power-on by HDMI and easy smart stick connection.
- **Fit and forget reliability**
Easy installation with multi-projection and signage function.
- **The complete solution**
With an incredible contrast ratio of 5,000,000:1, the EB-L260F delivers vivid, lifelike content and defined shadow detail with deeper blacks

PRODUCT SPECIFICATIONS

EB-L260F

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.62 inches with C2 Fine
IMAGE	
Color Light Output	4600 Lumens - 3200 Lumens (economy)
White Light Output	4600 Lumens - 3200 Lumens (economy)
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.32 - 2.12:1
Zoom	Digital, Factor: 1 - 1.62
Lens	Optical
Screen Size	31 in - 310 in
Projection Lens F Number	1.77
Projection Lens Focal Length	29.1 mm
Projection Lens Focus	Manual
Offset	10 : 1
CONNECTIVITY	
Interfaces	VGA in (2 x), Composite in (1 x), USB 2.0-A (1 x), Microphone input (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), RS-232C (1 x), VGA out (1 x), Miracast (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), Cinch audio out (1 x), USB 2.0 (1 x), Jack plug in (2 x), Jack plug out (1 x), Wi-Fi Direct (1 x), HDMI (HDCP 2.2) (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink, HTTPS, IPv6, SNMP, ESC/VP.net
ADVANCED FEATURES	
Security	Kensington lock, Security cable hole, Wireless LAN unit lock, Padlock, Security bar, Control panel lock, Password protection, Wireless LAN security
Other Features	AV Mute Slide, Auto source search, Built-in speaker, Customizable user logo, Document Camera Compatible, Home Screen, Long light source life, OSD copy function, PC Free, Quick Corner, Screen share, Screen Mirroring, Split-Screen-Function, Wireless LAN capable, iProjection App, Arc Correction, Auto Power On, Direct Power on/off, Edge Blending, Horizontal and vertical keystone correction, Schedule Function, Super resolution, Web Control, CEC compatible
Video Colour Modes	Cinema, Dynamic, Presentation, sRGB, DICOM SIM, Blackboard, Multi Projection
Projector Control	Extron IP Link, Control4 Simple Device Discovery Protocol, AMX Device Discovery, Crestron Integrated Partner

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	199 W, 260 W (economy), 144 W (standby)
Heat Dissipation	884 BTUperhour
Product dimensions	325 mm x 299 mm x 90 mm (Width x Depth x Height)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection, Epson Projector Management, Epson Creative Projection, Epson Projector Content Manager
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wall mount
Loudspeaker	16 W
Room Type / Application	Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Positioning	Desktop, Ceiling Mounted, Floor, Wall Mounted
Colour	White

OTHER

EB-L260F

WHAT’S IN THE BOX

- Remote control incl. batteries
- Power cable
- Main unit
- HDMI Cable
- Warranty card
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series V13H134A60
- Ceiling mount / Floor stand - ELPMB60B V12H963110
- Ceiling mount / Floor stand - ELPMB60W V12H963210
- Ceiling pipe - ELPFP13 - 668-918mm V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm V12H003P14
- Control and Connection Box - ELPCB03

- Control and Connection Box - ELPCB03 [240v] V12H927040DA
- Control and Connection Box - ELPCB03N V12HB11040
- External Speaker - ELPSP02 V12H467040
- External Speaker - ELPSP02 - [240v] V12H467040DA

