EB-L690U

DATASHEET / BROCHURE



EB-L690U

Ідеально для конференц-залів і лекційних аудиторій. Лазерний 3LCD-проєктор WUXGA з широким зміщенням об’єктива та тихою роботою.

KEY FEATURES

Ідеально для конференц-залів, лекційних аудиторій і не тільки. Цей компактний бюджетний лазерний проєктор забезпечує високоякісну продуктивність у будь-якій обстановці.

- **Компактний дизайн з масштабованими зображеннями до 500”**

  Легкий дизайн спрощує транспортування та встановлення, забезпечуючи масштабовані зображення до 500” для максимальної гнучкості.

- **Просте, гнучке встановлення**

  З фіксованим центральним об’єктивом, широким зміщенням об’єктива та просунутими функціями налаштування просте й адаптивне до будь-якого середовища.

- **Тиха робота**

  Насолоджуйтеся високопродуктивним проєктором із низьким рівнем шуму 25 дБ в Eco-режимі — для тихої, зосередженої атмосфери на презентаціях і зустрічах.

- **Вибір сталого розвитку з Epson**

  Проєктор виготовлено на 19% з переробленої пластмаси, він має низьке енергоспоживання, меншу упаковку та термін служби до 30 000 годин у режимі Eco (20 000 годин у нормальному режимі).

PRODUCT SPECIFICATIONS

EB-L690U

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	6500 Lumens - 4550 Lumens (economy)
White Light Output	6500 Lumens - 4550 Lumens (economy)
Resolution	WUXGA
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	HDBaseT (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), HDMI out (1 x), USB 2. Type B (Service Only) (1 x), Near Field Communication (NFC) (1 x), RS-232C (1 x), Jack plug out (1 x), Miracast (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), HDMI (HDCP 2.3) (2 x), USB 2.-A (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	SNMP, HTTPS, PJLink, ESC/VP.net
ADVANCED FEATURES	
Security	Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, Control panel lock
Other Features	21:9 aspect ratio support, A/V mute, Auto Power On, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App, Screen Mirroring
Video Colour Modes	Dynamic, Presentation, Cinema, BT79, Natural, DICOM SIM, Multi Projection
Projector Control	Extron XTP, AMX Device Discovery, Crestron Integrated Partner

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	336 W, 233 W (economy), 0.4 W (standby)
Product dimensions	440 mm x 340 mm x 138 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 32 dB (A) - Economy: 25 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Suspension adapter
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User manual
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
  V13H134AF0
- Cable Cover - ELPCC07W-White - L6/7/89x Series
  V12H003AP0
- Camera Unit - ELPEC01
  V12HA46010
- Ceiling Mount - ELPMB22 - White
  V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
  V12H526040
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]

- Safety Wire - ELPWR01
  V12H003W01

EPSON®