



# Epson EB-770F



## KEY FEATURES

### Scalable FHD display for any room •

UST display for unrestricted 79-150 viewing (no shadows/reflections)

### Bright and energy efficient laser •

4,100lm CLO with 3LCD technology for brighter colours at only 205W

### Effortless connectivity options •

Auto-on, wired / wireless display with USB 2A output for smart sticks

### Simple to use and built to last •

Virtually maintenance free with 5-year, 12,000hr warranty

### Document camera compatibility •

Create and record a live, totally immersive lesson or presentation

EB-770F

### Best for meeting rooms and classrooms. Ultra-short-throw laser display .with 4,100 lumens and wireless connectivity

The EB-770F's ultra short throw lens allows safe, discreet positioning close to the display, enabling presenters free access to perform without casting shadows. With 4,100 lumens CLO and 3LCD technology, the display is bright and vibrant up to 150", clearly visible from all angles and at a distance. The experience is immersive and user-friendly. Scalable from 49-150", display sizes can be optimised for each room with one product and a fixed cost, and the EB-770F supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image. Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room. Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots at certain angles, and teachers are not subjected to LCD panel direct blue light radiation, believed to damage eyes. Paired with a hygienic, antibacterial whiteboard, teachers can annotate presentations with dry-wipe pens, or to save energy, simply use the whiteboard with the display turned off.

TECHNOLOGY	
تقنية 3LCD عطاء عدسة الكريستال السائل من RGB	Projection System
inches with C2 Fine 0.62	LCD Panel

IMAGE	
Color Light Output	Lumens - 2800 Lumens (economy) 4100
White Light Output	Lumens - 2800 Lumens (economy) 4100
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	الليزر
Laser Light source	hr Durability High, 30000 hr Durability Eco 20000
Keystone Correction	Manual vertical: 3, Manual horizontal: 3
Colour Video Processing	Bits Color 10
Colour Reproduction	Upto 1.07 billion colours

OPTICAL	
0.35:1 - 0.25	Throw Ratio
Digital, Factor: 1 - 1.35	Zoom
بصري	Lens
in - 150 in 60	Screen Size
1.6	Projection Lens F Number
mm 3.7	Projection Lens Focal Length
Manual	Projection Lens Focus
1 : 5	Offset

CONNECTIVITY	
شبكة محلية لاسلكية (1 x), USB 2 (1 x), LAN IEEE 802.11a/b/g/n/ac (WiFi 5 (1 x)), VGA (2 x), مخرج صوت بمقياس استريو صغير (1 x), مخرج صوت بمقياس استريو كبير (2 x), منفذ USB 2 من الفئة A (2 x), توجيه (1), Miracast (1 x), Wi-Fi (1 x), Composite (1 x), واجهة توصيل Ethernet (1 Base-TX/1 Base-T) (1 x), مخرج (1 x) VGA, مخرج ميكروفون (1 x), مخرج صوت بمقياس استريو صغير (3 x), RS-232C (1 x)	Interfaces
بنية تقنية/مخصصة لأغراض معينة	Epson iProjection App
IPv6, PjLink, ESC/MP.net, SNMP, HTTPS, IPv4	Network Protocol

ADVANCED FEATURES	
حماية كينسينغتون, Padlock, فتحة كابل الحماية, قفل وحدة LAN لاسلكية, حماية كلمة المرور, أمان شبكة LAN لاسلكية, إغلاق لوحة التحكم	Security
AV mute, تصحيح محاذاة الانحناء, تشغيل تلقائي, البحث التلقائي عن المصدر, سماعات مدمجة, شعار المستخدم القابل للتخصيص, زوم رقمي, التشغيل/إيقاف التشغيل المباشر, دمج للحواف, كاميرا الوثائق المتوافقة, Email notification, تصحيح انحراف أفقي ورأسي, إزاحة الصورة وتصحيح JPEG, عدسة بقاء المصدر, ضوء, وظيفة النسخ المعوض, ضوء على الشاشة, عرض صورة, عدسة الشبكة بدون كمنود	Other Features

## WHAT'S IN THE BOX

- كابل للكهرباء
- التحكم عن بعد مع بطاريات
- Projector feet
- دليل التشغيل السريع
- وثيقة الضمان

## OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  - V13H134A60
- Ceiling Mount - ELPMB23 - White
  - V12H003B23
- Ceiling pipe - ELPFP13 - 668-918mm
  - V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  - V12H003P14
- Control and Connection Box - ELPCB03
  - V12H927040
- Control and Connection Box - ELPCB03 [240v]
- Control and Connection Box - ELPCB03N
  - V12HB11040DA
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx
  - V12HA06A06
- External Speaker - ELPSP02
  - V12H467040
- External Speaker - ELPSP02 - [240v]

## Wireless Presentation Systems

## GENERAL

Power consumption	W, 263 W (economy), 141 W (standby) 197
Product dimensions	mm x 395 mm x 133 mm (Width x Depth x Height) 356
Heat Dissipation	BTUperhour 895
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	% Operation 20 % - 80 %, Storage 10 % - 90
Options	حامل التركيب على الحائط
Loudspeaker	W 16
Room Type / Application	اللاقتات / البيع بالتجزئة, مناطق جذب الزوار, غرفة اجتماعات / قاعة دراسية, Home Office, غرفة اجتماعات
Positioning	تركيب في السقف, سطح المكتب, تركيب على الحائط, تثبيت على الطاولة
Colour	White

## OTHER

## LOGISTICS INFORMATION

V11HA79080	SKU
8715946715841	EAN Code
Philippines	Country Of Origin