EB-L630SU

DATASHEET / BROCHURE





EB-L630SU

Ідеально для професійних середовищ. Короткофокусний лазерний 3LCD-проєктор Full HD з яскравістю 6000 люменів і гнучким встановленням.

Забезпечуючи сміливіші, яскравіші, привабливіші та впливовіші дисплеї навіть у яскраво освітлених середовищах, EB-L630SU пропонує вражаючу яскравість 6000 люменів і роздільну здатність WUXGA Full HD за доступною ціною. Це означає, що користувачі можуть оновитися до лазерної продуктивності та надійності зі зменшеним споживанням енергії, не переплачуючи. Він також має: відношення проєціювання 0.8:1, підтримку входу 4K, технологію покращення деталізації, зрощення країв і широке зміщення об’єктива для відповідності складним середовищам встановлення. EB-L630SU здатний створювати великоформатні та зрощені дисплеї без зниження ясності або насиченої деталізації. Це рішення для відображення пропонує багато різних способів підключення, одночасного показу кількох джерел і бездротового представлення. EB-L630SU оснащено готовими до майбутнього варіантами підключення, зокрема HDMI і HDBaseT з підтримкою сигналу 4K, бездротовим зв’язком 5 ГГц з корпоративною безпекою, оновленим Miracast, вбудованим медіаплеєром і підтримкою бездротової презентаційної системи ELP-WP10 від Epson. Цей стильний і компактний проєктор підтримує встановлення під кутом 360 градусів без шкоди для якості відображення та підтримує ультраширокий екран 16:6, вихід HDMI та зрощення країв для інсталяцій з кількох проєкторів. Також доступний у чорному кольорі.

KEY FEATURES

- **Яскравість 6000 люменів**

  Чіткі зображення та яскраві кольори навіть у добре освітлених кімнатах

- **Роздільна здатність WUXGA**

  Чіткі зображення Full HD для виняткової ясності

- **Готові до майбутнього варіанти підключення**

  Підтримка входу 4K, HDMI, HDBaseT, інтегрований Wi-Fi і дзеркалювання екрана

- **Просте, гнучке встановлення**

  Легкий і компактний дизайн з широким зміщенням об’єктива

- **Короткофокусна проєкція**

  Велике зображення в тісних приміщеннях (відношення відстані до розміру на рівні 0,8:1)

EPSON

PRODUCT SPECIFICATIONS

EB-L630SU

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	6000 Lumens - 4200 Lumens (economy)
White Light Output	6000 Lumens - 4200 Lumens (economy)
Resolution	WUXGA
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.8 - 1.07:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	50 in - 200 in
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	USB 2. (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), HDMI (HDCP 2.3) (2 x), VGA in (2 x), USB 2.-A (1 x), RS-232C (1 x), HDMI out (1 x), USB 2 Type A playback (1 x), VGA out (1 x), Miracast (1 x), Jack plug out (1 x), Wireless LAN a/n (5GHz) (1 x), Jack plug in (2 x), HDBaseT (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	IPv6, ESC/VP.net, PJLink, SNMP, HTTPS
ADVANCED FEATURES	
Security	Kensington lock, Wireless LAN unit lock, Control panel lock, Security cable hole, Wireless LAN security, Password protection
Other Features	A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Super resolution, Ultra-wide display (16:6), Volume control, Web Control, Web Remote, Wireless LAN capable, iProjection App, CEC compatible, 21:9 aspect ratio support
Video Colour Modes	Dynamic, Cinema, sRGB, Presentation, DICOM SIM, Multi Projection
Projector Control	AMX Device Discovery, Control4 Simple Device Discovery Protocol, Extron XTP, Extron IP Link, Crestron Integrated Partner

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	287 W, 164 W (economy), 0.3 W (standby)
Product dimensions	440 mm x 334 mm x 136 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 38 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Document camera, HDBaseT Transmitter, Wireless LAN unit, External Speaker, MB22 ceiling mount
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User guide
- Warranty Documents
- Main unit
- HDMI Cable

OPTIONAL ACCESSORIES

- Air Filter - ELPAF56 - L600/EB-14XX Series
  V13H134A56
- Ceiling Mount - ELPMB22 - White
  V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
  V12H526040
- Ceiling Mount - ELPMB68
  V12H006AE0
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Extension Pole - ELPMB70 - For ELPMB68
  V12H006AG0
- Portrait Adaptor - ELPMB69 - For ELPMB68
  V12H006AF0
- Safety Wire - ELPWR01
  V12H003W01
- Truss Adaptor - ELPMB71 - For ELPMB68
  V12H006AH0

EPSON®