

EB-PU2213B

DATASHEET / BROCHURE



EB-PU2213B

Orta-büyük mekân kurulumları için ideal. 4K enhancement ve IP5X sertifikasıyla kompakt 13.000 lümen WUXGA 3LCD lazer projektör.

13.000 lümen parlaklık ve WUXGA çözünürlük sunan EB-PU2213B, büyük ölçekli kurulumlar için tasarlanmış kompakt bir lazer projektördür. 4K enhancement teknolojisi sayesinde keskin, yüksek kontrastlı görüntüler üretir; geniş bir Epson değiştirilebilir lens yelpazesi ile uyumludur. Kenar harmanlama, istifleme ve lens esnekliğinin önemli olduğu çoklu projektör kurulumlarında olağanüstü esneklik sunar. Epson Projector Professional Tool, yansıtma haritalama gibi gelişmiş teknikleri kolaylaştırır; NFC desteği Epson Projector Config Tool ile teşhis ve kurulumu basitleştirir. IP5X sertifikalı toz dirençli yapı, zorlu ortamlarda kur-ve-unut güvenilirliği sağlar.

KEY FEATURES

• Ultra hafif ve kompakt

Depolama, taşıma ve kurulumu kolay

• Etkileyici görüntü ekranları

13.000 lm, 4K Enhancement teknolojisi, WUXGA çözünürlük

• Kullanımı kolay

Basit kurulum, istifleme, lens esnekliği ve kontrol

• Kur-ve-unut güvenilirliği

Geliştirilmiş toz dirençli yapı — IP5X sertifikalı

• Екологічні переваги

Менше споживання енергії, менша упаковка, менша вага

PRODUCT SPECIFICATIONS

EB-PU2213B

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	1.03 inches with C2 Fine
IMAGE	
Color Light Output	13000 Lumens - 9100 Lumens (economy)
White Light Output	13000 Lumens - 9100 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.35 - 7.41:1
Zoom	Digital, Factor: 1 - 1.6
Screen Size	60 in - 1000 in
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	USB content playback (1 x), 3G-SDI Input (1 x), RS-232C (1 x), 3G-SDI Output (1 x), Ethernet Interface (1 Base-T/ 1-Base TX/ 1-Base-T) (1 x), Wireless LAN IEEE 802.11a/b/g/n (Optional), Remote (1 x), HDBaseT (1 x), Near Field Communication (NFC) (1 x), HDMI in (1 x), Jack plug out (1 x), VGA in (1 x), DVI in (1 x), USB 2.-A (2 x), USB 2. Type B (Service Only) (1 x)
Network Protocol	IPv6, ESC/VP.net, PJLink, HTTPS, SNMP
ADVANCED FEATURES	
Security	Kensington lock, Security bar, Password lock, Password protection, Wireless LAN unit lock, Wireless LAN security
Other Features	4K enhancement, Auto Power On, Auto source search, Direct Power on/off, Edge Blending, Long light source life, Lens position memory, OSD copy function, Power on button, Schedule Function, Quick Corner, Super resolution, Split-Screen-Function, Web Control, Web Remote, iProjection App, 21:9 aspect ratio support, Point correction, Freeze image, Horizontal and vertical keystone correction
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT79
Projector Control	AMX, Crestron, Extron

PRODUCT SPECIFICATIONS

GENERAL	
Product dimensions	586 mm x 492 mm x 218 mm (Width x Depth x Height)
Heat Dissipation	2,938 BTUperhour
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Creative Projection, Epson Projector Content Manager, Epson Projector Manage-ment, Epson Projector Professional Tool, Epson Projector Config Tool
Noise Level	Normal: 34 dB (A) - Economy: 29 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Ceiling mount, Wireless LAN unit, Camera module
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Map-ping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Flying Frame
Colour	Black

OTHER

EB-PU2213B

WHAT’S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- Document Pack
- Initial toner cartridges
- Main unit
- Quick Start Guide

OPTIONAL ACCESSORIES

- Camera Unit - ELPEC01
V12HA46010
- Ceiling Mount - ELPMB68
V12H006AE0
- Extension Pole - ELPMB70 - For ELPMB68
V12H006AG0
- Lens - ELPLL08 - Long throw - EB-PU Series
V12H004L08
- Lens - ELPLM10 - Mid throw 3 - EB-PU Series
V12H004M0A
- Lens - ELPLM11 - Mid throw 4 - EB-PU Series
V12H004M0B
- Lens - ELPLM15 - Mid throw - EB-PU Series
V12H004M0F
- Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
V12H004UA3
- Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series
V12H004U04
- Lens - ELPLW05 - Wide zoom 1 - EB-PU Series
V12H004W05