EB-800F



DATASHEET / BROCHURE

LASER

EB-800F

Best for digital signage in retail and public spaces. Ultra-short-throw Full HD laser projector with 5,000 lumens and 360-degree rotation.

Epson's advanced laser technology is robust and reliable, providing a fit-and-forget digital signage solution. It offers bright and vivid colours in a cost-effective solution that's capable of large display sizes.The EB-800F enables scalable display sizes of up to 130 inches, in Full HD resolution with 5,000 lumen brightness and 3LCD technology for bright colours and high display quality even in bright spaces.This sleek, stylish and bright display solution offers the flexibility to fulfil the most exacting brief, and the versatility to work in tight spaces. It can be mounted on the wall, ceiling, floor, or even hidden away to create added mystery. Its ultra-short-throw design enables projection of large images from a short distance. A black version is also available. Content can be played directly from a USB stick, including: playlists, videos, and signage content using the built-in content playback feature and Epson Projector Content Manager software. Users can benefit from multi-projector and daisy-chain support for built-in edge blending, or illuminate an entire wall with one huge image. Also, the split screen feature allows users to connect multiple input sources to display different content sources simultaneously.

KEY FEATURES

- **Ultra-short-throw signage projector**

  Compact, unobtrusive design.
- **Up to 130-inch display**

  Full HD resolution, 5,000 lumen brightness and 3LCD technology
- **Fit and forget reliability**

  Low maintenance laser projector with a 5 year warranty
- **Easy installation**

  360 degree rotation with portrait projection support
- **Flexible playback**

  Play content directly from a USB stick

EPSON®

PRODUCT SPECIFICATIONS

EB-800F

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.62 inches with C2 Fine
IMAGE	
Color Light Output	5000 Lumens - 3500 Lumens (economy)
White Light Output	5000 Lumens - 3500 Lumens (economy)
Resolution	1080p
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 3, Manual horizontal: 3
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.27 - 0.37:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	65 in - 130 in
Projection Distance Wide	0.4 m (65 inch screen)
Projection Distance Tele	0.8 m (130 inch screen)
Projection Lens F Number	1.5
Projection Lens Focal Length	3.9 mm
Projection Lens Focus	Manual
Offset	9 : 1
CONNECTIVITY	
Interfaces	Composite in (1 x), Jack plug out (1 x), Jack plug in (3 x), VGA in (2 x), Powered USB (1 x), HDMI in (3 x), USB 2.0 (1 x), HDMI out (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (Optional), VGA out (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0-A (2 x), Miracast (Optional), HDBaseT (1 x), RS-232C (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv6, SNMP, PJLink, ESC/VP.net
ADVANCED FEATURES	
Security	Kensington lock, Security cable hole, Password lock, Password protection, Padlock
Other Features	Arc Correction, Quick Corner, Auto Power On, Auto source search, Built-in speaker, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Edge Blending, Horizontal and vertical keystone correction, Long light source life, Split-Screen-Function, Ultra-wide display (16:6), Web Remote, Direct Power on/off, Document Camera Compatible, Driverless installation, Image Shift, OSD copy function, Network administration, Schedule Function, Web Control, Email notification, iProjection App, Home Screen, A/V mute, JPEG Viewer, Network projection, PC Free, Power on button
Video Colour Modes	Cinema, Dynamic, Presentation, sRGB, Blackboard, DICOM SIM, Multi Projection
Projector Control	Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol, Crestron Integrated Partner, Crestron RoomView

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	293 W, 194 W (economy), 0.5 W (standby)
Heat Dissipation	1,244 BTUperhour
Product dimensions	458 mm x 375 mm x 209.5 mm (Width x Depth x Height)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Management, Epson Projector Content Manager
Noise Level	Normal: 36 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wireless LAN unit
Loudspeaker	8 W
Room Type / Application	Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Wall Mounted
Colour	White

OTHER

WHAT'S IN THE BOX

- CD Manual
- Remote control incl. batteries
- Cable cover
- Power cable
- Warranty document
- Lens cap
- Projector feet

OPTIONAL ACCESSORIES

- Air Filter - ELPAF56 - L600/EB-14XX Series
  V13H134A56
- Control and Connection Box - ELPCB03
  V12H927040
- Control and Connection Box - ELPCB03 [240v]
- Control and Connection Box - ELPCB03N
  V12HB11040
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx
  V12HA06A06
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]
- Wireless LAN Adapter - ELPAP11 (2.4GHz & 5GHz)
  V12H005A01

EPSON®