Epson EB-L210SW

DATASHEET / BROCHURE



EB-L210SW

Ідеально для класів і конференц-залів. Короткофокусний лазерний проєктор WXGA з 4000 люменами та бездротовим підключенням.

Короткофокусний об'єктив EB-L210SW дозволяє близьке розміщення проєктора до дисплея, ідеально для невеликих кімнат і зниження ризику тіней на дисплеї. На відміну від проєкторів деяких інших брендів, EB-L210SW має технологію 3LCD, що забезпечує яскравість кольорового та білого світлового потоку 4000 люменів для яскравого та насиченого дисплея. Враження занурювальне та зручне для користувача. Масштабований від 53 до 120", розміри дисплея можна оптимізувати для кожної кімнати з одним продуктом і фіксованою вартістю, а також створює великий дисплей до 125", чітко видимий з усіх кутів і на відстані. EB-L210SW може бути портативним, а тут немає скляної плоскої панелі, яка створює відбиваючі сліпі плями під певними кутами. Універсальні варіанти дротового та бездротового підключення, зокрема дзеркалювання екрана Miracast™, забезпечують безпроблемний обмін контентом між кількома пристроями, а з підключеним опціональним візуалізатором Epson документи, презентації або 3D-об'єкти можна проєціювати з неймовірною деталізацією для всієї кімнати. З виходом USB 2A потужності також можна підключати HDMI-стрімінгові стики, щоб відкрити подальші можливості.

KEY FEATURES

- **Масштабований, портативний HD дисплей**

  53–120" короткофокусний дисплей для безперешкодного перегляду без відблисків

- **Яскравий і енергоефективний лазер**

  4000 лм CLO з технологією 3LCD для яскравіших кольорів при лише 201 Вт

- **Прості варіанти підключення**

  Авто-ввімкнення, дротовий/ бездротовий дисплей із USB 2A виходом для смарт-стиків

- **Простий у використанні та створений довго служити**

  Практично безобслуговувальний із 5-річною гарантією на 12 000 годин

- **Сумісність із документ-камерою**

  Створюйте та записуйте живі уроки або презентації з ефектом присутності

PRODUCT SPECIFICATIONS

Epson EB-L210SW

TECHNOLOGY	
Projection System	3LCD Technology Consists of LCD/Back lighting
LCD Panel	0.59 inches with C2 Fine
IMAGE	
Color Light Output	4000 Lumens - 2800 Lumens (economy)
White Light Output	4000 Lumens - 2800 Lumens (economy)
Resolution	WXGA 2
High Definition	HD ready
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 15, Manual horizontal: 15
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.48 - 0.65:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	55 in - 120 in
CONNECTIVITY	
Interfaces	Microphone input (1 x), HDMI in (2 x), USB 2. (1 x), USB 2. Type B (Service Only) (1 x), RS-232C (1 x), VGA out (1 x), Wi-Fi Direct (1 x), VGA in (2 x), Jack plug in (2 x), Jack plug out (1 x), Ethernet Interface (1 Base-T/ 1-Base TX/ 1-Base-T) (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), Miracast (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other Features	Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Instant on/off, Mail notification function, Microphone input, Network administration, Long light source life, OSD copy function, Quick Corner, Network projection, Split-Screen-Function, Set-up wizard, Screen Mirroring, Web Control, Web Remote, Wireless LAN capable, iProjection App
Video Colour Modes	Blackboard, Dynamic, Presentation, sRGB, Cinema
Projector Control	AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol, Crestron RoomView

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	201 W, 144 W (economy), 0.5 W (standby)
Product dimensions	325 mm x 337 mm x 90 mm (Width x Depth x Height)
Heat Dissipation	884 BTUperhour
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Management, EasyMP Multi PC Projection, Epson Projector Content Manager
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Visualiser camera, Wall mount, External Speaker, Ceiling mount
Loudspeaker	16 W
Room Type / Application	Meeting room / Classroom
Positioning	Wall Mounted, Table Mounted, Ceiling Mounted
Colour	White

OTHER

Epson EB-L210SW

WHAT'S IN THE BOX

- HDMI Cable 1.8m
- Quick Start Guide
- Remote control incl. batteries
- Power cable
- Warranty Documents

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  V13H134A60
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB03
  V12H927040
- Control and Connection Box - ELPCB03 [240v]

- Control and Connection Box - ELPCB03N
  V12HB11040
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]

- Soft Carry Case - ELPKS71
  V12H001K71
- Wall Mount - ELPMB64 - EB-L2xx
  V12HA39010

EPSON®