EB-L795SE

DATASHEET / BROCHURE



EB-L795SE

Best for professional environments. 7,000-lumen 4K Enhanced 3LCD short-throw laser projector with flexible installation.

KEY FEATURES

Delivering sharp, bright images with up to 4.6 million pixels, this budget-friendly laser display is perfect for large displays in professional spaces.

- **Compact short-throw design for immersive display**

  Project scalable images up to 400”, creating immersive, shadow- and glare-free visuals in compact spaces with a short throw ratio of 0.79–1.36:1 and 1.7x zoom.

- **Quiet operation**

  Delivers high-performance display at a low noise level of 36dB or 26dB in Eco mode, ensuring a quiet and focused environment for immersive visual experiences.

- **Effortless, flexible installation**

  A fixed centre lens with manual lens shift and advanced features like corner focus adjustment ensures easy setup and adaptability for any environment.

- **Making sustainable choices with Epson**

  Made from 19% recycled plastics, low power consumption, reduced packaging and a usage life of up to 30,000 hours in Eco mode (20,000 hours normal).

EPSON®

PRODUCT SPECIFICATIONS

EB-L795SE

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	7000 Lumens - 4900 Lumens (economy)
White Light Output	7000 Lumens - 4900 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.79 - 1.36:1
Zoom	Digital, Factor: 1 - 1.7
Lens	Optical
Screen Size	60 in - 400 in
Projection Lens F Number	2.1
Projection Lens Focal Length	19.9 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	Miracast (1 x), RS-232C (1 x), HDMI out (1 x), HDBaseT (1 x), USB 2.0-A (2 x), HDMI (HDCP 2.3) (2 x), Jack plug out (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0 Type B (Service Only) (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection
Other Features	21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App, Screen Mirroring
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector Control	Crestron Integrated Partner, Extron XTP, AMX Device Discovery

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	388 W, 266 W (economy), 0.4 W (standby)
Product dimensions	440 mm x 362 mm x 151 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 36 dB (A) - Economy: 26 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Air filter, Camera module, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP20
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Sports, Gaming, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	Black

OTHER

EB-L795SE

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User guide
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
  V13H134AF0

EPSON®