

WorkForce Pro WF-C878RDTWF



WorkForce Pro WF-C878RDTWF

Best for offices that need high-yield colour printing with reduced downtime and fewer supply changes.

High yield printing.

This low-intervention MFP prints up to 20,000 pages in mono or colour without changing the ink supplies.¹ This means there is low user intervention, increasing productivity.

Precision Core Heat-free technology.

Epson Heat-Free Technology requires no heat to warm up when it is switched on or woken from sleep, which significantly reduces energy consumption and therefore saves money. This also means Epson's Heat-Free inkjets can deliver a fast first page out time (FPOT) of 5.5 seconds compared to laser printers, which need to preheat the fuser to print.

Enhance functionality with in-house (EDA, EPA) and third party solutions (Open Platform)

Gain complete control of printing operations with Epson and its partners solutions, allowing devices to be set up to meet specific and changing business requirements.

Epson Remote Services (ERS)

Our cloud-based device monitoring and management system helps service providers to perform accurate remote diagnosis without compromising on security. The embedded agent on the WF-C878R allows for seamless setup and use.

KEY FEATURES

- **High reliability**

With few moving parts, and low intervention, increase printer uptime

- **High print yield**

Print up to 20,000 pages without changing the supplies¹

- **Low power consumption**

Epson's Heat-Free technology uses no heat, reducing energy consumption

- **Epson Remote Services**

Cloud-based, advanced diagnosis of Epson printers and MFPs.

PRODUCT SPECIFICATIONS

TECHNOLOGY

| | |
|----------------------|--|
| Printing Method | PrecisionCore™ Print Head |
| Minimum Droplet Size | 4.6 pl, With Variable-Sized Droplet Technology |
| Ink Technology | Replaceable Ink Pack System (RIPS) |
| Printing Resolution | 4800 x 1200 DPI |

PRINT

| | |
|------------------------------|--|
| Printing Speed ISO/IEC 24734 | 25 Pages/min Monochrome, 24 Pages/min Colour |
|------------------------------|--|

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

| | |
|--------------|----------------------------|
| Scanner Type | Contact image sensor (CIS) |
|--------------|----------------------------|

PAPER / MEDIA HANDLING

| | |
|----------------|--|
| Paper Formats | A3+ |
| Duplex | Yes |
| Print Margin | 0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.) |
| Media Handling | Rear specialty media feed, Thick Media Support, Automatic duplex (A4/A3, plain paper), Portrait & Landscape printing |

GENERAL

| | |
|------------------------------------|---|
| Product dimensions | 621 mm x 652 mm x 769 mm (Width x Depth x Height) |
| Compatible Operating Systems | Windows Server 2016 |
| WLAN Security | WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES) |
| Mobile and Cloud Printing Services | Apple AirPrint, Google Cloud Print, Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud) |

OTHER FEATURES

| | |
|----------|---|
| Panel | Type: Colour, Diagonal: 12.7 |
| Features | Direct print from USB, Direct scan-to-print without PC, Touchscreen |

OTHER

LOGISTICS INFORMATION

| | |
|-------------------|---------------|
| SKU | C11CH60401BX |
| EAN Code | 8715946690681 |
| Country Of Origin | Indonesia |

WorkForce Pro WF-C878RDTWF

WHAT'S IN THE BOX

- Quick Setup Guide
- Main unit
- Warranty Documents
- User manual (CD)
- Power cable
- Paper tray
- Initialization Ink Supply Units

INK COMPATIBILITY

- WF-C869R/C878R/C879R Maintenance Box
- WorkForce Pro WF-C869R Optional Cassette Maintenance Roller
- WorkForce Pro WF-C869R Standard Cassette Maintenance Roller
- WorkForce Pro WF-C87xR Black XL Ink Supply Unit
- WorkForce Pro WF-C87xR Cyan XL Ink Supply Unit

INK YIELD DATA

Included

Replacement

¹Approx. page yield with the WF-C878R. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield.

EPSON[®]