Epson L15160 CIS

DATASHEET / BROCHURE



EcoTank Business+ L15160

Best for demanding businesses that need fast A3+ colour print, copy, scan and fax with high-volume handling.

KEY FEATURES

- **Fast, time-saving printing**

  Enjoy print speeds up to 25ipm in both black and colour[4]

- **Built for demanding businesses**

  High quality print, copy, scan and fax with large paper trays for low-intervention printing

- **Seamless connectivity**

  Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps

- **Epson Smart Panel app**

  Just add paper for low intervention printing!

- **Number 1 ink tank printer brand worldwide***

  80m EcoTank printers sold worldwide*

EPSON®

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Method	PrecisionCore™ Print Head
Ink Technology	Pigment ink
Printing Resolution	4800 x 1200 DPI
PRINT	
Printing Speed ISO/IEC 24734	25 Pages/min Monochrome, 25 Pages/min Colour
For detailed information on printing speeds please visit http://www.epson.eu/testing.	
SCAN	
Scanner Type	Contact image sensor (CIS)
PAPER / MEDIA HANDLING	
Paper Formats	A3+, A3 (29.7x42.0 cm), A4 (21.0x29.7 cm), A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, DL (Envelope), No. 10 (Envelope)
Duplex	Yes (A4/A3, plain paper)
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.)
Media Handling	ADF 2-sided copy (A4/A3, plain paper), ADF 2-sided fax (A4/A3, plain paper), ADF 2-sided scan (A4/A3, plain paper), Automatic duplex (A4/A3, plain paper), Borderless Print
GENERAL	
Product dimensions	515 mm x 500 mm x 350 mm (Width x Depth x Height)
Compatible Operating Systems	Windows 10 (32/64 bit), Windows 8.1 (32/64 bit), Windows 8 (32/64 bit), Windows 7 (32/64 bit), Windows Vista (32/64 bit), Windows XP SP3 or later (32-bit), Windows XP Professional x64 Edition SP2 or later, Windows Server 2003 SP2 or later, Windows Server 2003 R2, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Mac OS X 10.6.8 or later, XP Professional x64 Edition SP2
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP)
Mobile and Cloud Printing Services	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint, Google Cloud Print
OTHER FEATURES	
Panel	Type: Colour, Diagonal: 10.9
Features	Touchscreen
OTHER	

LOGISTICS INFORMATION

Epson L15160 CIS

WHAT'S IN THE BOX

- 1 set of ink (1x 127ml BK, 3x 70ml cmY)
- Main unit
- Power cable
- Quick Start Guide
- User manual

INK COMPATIBILITY

- 112 EcoTank Pigment Black ink bottle
- 112 EcoTank Pigment Cyan ink bottle
- 112 EcoTank Pigment Magenta ink bottle
- 112 EcoTank Pigment Yellow ink bottle

INK YIELD DATA

Included	* 4,500 Pages	* 2,800 Pages
Replacement		

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.

1. Compared to best-selling similarly-featured printers in Middle East & Africa (IDC, Quarterly Hardcopy Peripherals Tracker, Q1 2023 to Q4 2023 shipments, published Q1 2024). Comparison based on the average yield when printing. Cost per page calculated by dividing the relevant bottle/cartridge average selling price as tracked by IDC by the yield. Epson models included: Eco Tank 112 Ink Bottle Series, Eco Tank 110 Ink Bottle Series, Eco Tank 101 Ink Bottle Series, Eco Tank 103 Ink Bottle Series, Eco Tank 664 Ink Bottle Series.
2. Mobile printing solutions require a wireless and/or an Internet connection to the printer. For a list of Epson Connect enabled printers, compatible devices, apps and ways to connect, visit www.epson.com/eme
3. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.
4. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.com/eme

EPSON®