
Epson L132 CIS

DATASHEET / BROCHURE



EcoTank Home L132

Best for families who want effortless, ultra-low-cost colour printing in a compact, reliable design.

The Epson EcoTank L132 is a cartridge-free colour printer designed for everyday home use. Save up to 90% on ink costs compared to cartridge printers, with up to three years' worth of ink included. Compact and easy to set up, it's the reliable choice for students, families and home users.

Say goodbye to cartridges.

EcoTank provides hassle-free home printing with ultra-high-capacity ink tanks. Mess-free refills and key-lock bottles are designed so only the correct colour can be inserted. Save up to 90% on ink costs compared to traditional cartridge printers.

Trusted by families.

With Epson Smart Panel, you can set up, print and scan from your phone in minutes. Compact and reliable, it fits seamlessly into your home and keeps up with the demands of everyday family life.

KEY FEATURES

- **Ultra-low-cost printing**
Integrated ultra-high-capacity ink tank
- **Two years of ink included¹**
4,500 pages in black and 7,500 pages in colour²
- **High quality, reliable results**
Micro Piezo technology and Epson genuine ink
- **Peace of mind**
Covered by Epson's 12 month or 15,000 page warranty
- **User friendly**
Hassle-free with simple set-up and maintenance

EPSON[®]

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	On-demand inkjet (Piezo electric)
Minimum Droplet Size	3 pl, With Variable-Sized Droplet Technology
Ink Technology	Dye Ink
Printing Resolution	5760 x 1440 DPI

PRINT

Printing Speed ISO/IEC 24734	7 Pages/min Monochrome, 3.5 Pages/min Colour
------------------------------	--

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

PAPER / MEDIA HANDLING

Paper Formats	User defined
Duplex	Manual
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.)
Paper Tray Capacity	10 Photo Sheets, 50 Sheets Standard
Media Handling	Borderless Print

GENERAL

Product dimensions	482 mm x 222 mm x 130 mm (Width x Depth x Height)
Noise Level	5.2 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 39 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode
Compatible Operating Systems	Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows Vista, Windows XP, Windows XP x64, Mac OS X 10.6.8 or later, Windows 8.1, Windows 8.1 x64 Edition, Windows Vista x64, XP Professional x64 Edition

OTHER FEATURES

OTHER

LOGISTICS INFORMATION

SKU	C11CE58403
EAN Code	8715946546827
Country Of Origin	Philippines

Epson L132 CIS

WHAT'S IN THE BOX

- Power cable
- Setup guide
- Software (CD)
- 4 x 70ml individual ink bottles (Bk,C,Y,M)
- Main unit
- Warranty document

INK COMPATIBILITY

- T6641 Black ink bottle 70ml
- T6642 Cyan ink bottle 70ml
- T6643 Magenta ink bottle 70ml
- T6644 Yellow ink bottle 70ml

INK YIELD DATA

Included

Replacement

* Quoted yields/ CPP are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC24712. Quoted yields/ CPP are NOT based on ISO/IEC24711. Quoted yields/ CPP may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature

1) 2 years of ink based upon user's average monthly print volume (IDC WW Page Volume Program, 2015)2) Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 with replacement sets of ink. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower.3) Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing

EPSON[®]