



Epson EB-770FI



KEY FEATURES

EB-770FI

Interactive FHD display for any room

UST display for unrestricted 90-100" viewing (no shadows/reflections)

Bright and energy efficient laser

4,100lm CLO with 3LCD technology for brighter colours at only 205W

Effortless connectivity options

Auto-on, wired / wireless display with USB 2A output for smart sticks

Simple to use and built to last

Virtually maintenance free with 5-year, 12,000hr warranty

Document camera compatibility

Create and record a live, totally immersive lesson or presentation

Best for collaborative workspaces and classrooms. Full HD ultra-short-throw interactive laser display with 4,100 lumens

The EB-770Fi is a step up from the EB-770F, with added interactive features.

Interactive technology enables two digital pens to be used on the display simultaneously (finger touch available through optional accessory FT01). Presentations can be controlled and brought to life with on-screen annotations, while a variety of convenient built-in tools support productivity. An optional Epson visualiser camera can be controlled via the display, projecting documents or objects from a desk for the whole room to see in incredible detail. With a 4,100 lumens laser-light source, combined with 3LCD technology, it produces a large, bright and vibrant display up to 100", clearly visible from all angles and at a distance. Versatile wired and wireless connectivity options, including screen mirroring via Miracast™, allows participants to effortlessly share content from their PCs or mobile devices. The experience is immersive and user-friendly. The ultra short throw lens allows safe, unobtrusive positioning above the display, enabling presenters free access to interact without casting shadows. Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots from certain angles; and presenters are not subjected to LCD panel direct blue light radiation

TECHNOLOGY	
تقنية 3LCD عطاء عدسة الكريستال السائل من RGB	Projection System
inches with C2 Fine 0.62	LCD Panel

IMAGE	
Color Light Output	Lumens - 2800 Lumens (economy) 4100
White Light Output	Lumens - 2800 Lumens (economy) 4100
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	الليزر
Laser Light source	hr Durability High, 30000 hr Durability Eco 20000
Keystone Correction	Manual vertical: 3, Manual horizontal: 3
Colour Video Processing	Bits Color 10
Colour Reproduction	Upto 1.07 billion colours

OPTICAL	
0.35:1 - 0.25	Throw Ratio
Digital, Factor: 1 - 1.35	Zoom
بصري	Lens
in - 100 in 60	Screen Size
1.6	Projection Lens F Number
mm 3.7	Projection Lens Focal Length
Manual	Projection Lens Focus
1 : 5	Offset

CONNECTIVITY	
واجهة توصيل Ethernet (1 Base-TX/1 Base-T) (1 x), واجهة اللمس المتعدد (Optional), توجيه RS-232C (1 x), Wi-Fi (1 x), مدخل ميكروفون (1 x), مخرج مزامنة (1 x), مدخل VGA (2 x), مدخل صوت بمقياس استريو صغير (3 x), شبكة محلية لاسلكية (LAN IEEE LAN IEEE), مدخل مزامنة (1 x), مخرج (1 x), مدخل VGA (1 x), مخرج (1 x), Composite (1 x), مدخل (3 x), HDMI, منفذ USB 2 من الفئة 2 (1 x), Miracast (1 x), A (2 x), النوع B (الخضمة فقط) (2 x), مخرج صوت بمقياس استريو صغير (1 x)	Interfaces
HTTPS, IPv4, SNMP, IPv6, ESC/VP.net, PJLink	Network Protocol

ADVANCED FEATURES	
حماية كينسينغتون, إغلاق لوحة التحكم, فتحة كابل الحماية, Padlock, أمان شبكة LAN لاسلكية, قفل وحدة LAN لاسلكية, حماية كلمة المرور, حماية كلمة المرور	Security
aspect ratio support, A/V mute 21:9, تصحيح محاذة الانحناء, تشغيل تلقائي, سماعات مدمجة, متوافق مع CEC, البحث التلقائي عن المصدر, زوم رقمي, التشغيل/الإيقاف التشغيل المباشر, دعم استخدام قلمين, الإعداد المسبق السهل المعروف على الشاشة, كاميرا الوثائق المتوافقة, Email notification, دعم اللمس بالإصبع, تطبيق Projection, إعداد Projection بواسطة QR, إمكانية توصيل بشبكة LAN لاسلكية, وظيفة مشاركة لوحة الكتابة, تحكم عبر الويب, التحكم عن بُعد عبر الويب, شاشة عرضة جذا (16:6), إنتاج الفيديو بجودة عالية	Other Features

WHAT'S IN THE BOX

- كابل للكهرباء
- حامل/قاعدة القلم
- أقلام تفاعلية
- 2 x رأس قلم (نفلون)
- 4 x رأس قلم (لبّاد)
- كابل USB
- التحكم عن بعد مع بطاريات
- دليل التشغيل السريع
- Projector feet
- وثيقة الضمان
- Corner markers for auto screen adjustment

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series •
V13H134A60
- Ceiling pipe - ELPPFP13 - 668-918mm •
V12H003P13
- Ceiling pipe - ELPPFP14 - 918-1168mm •
V12H003P14
- Control and Connection Box - ELPCB03 •
V12H927040
- Control and Connection Box - ELPCB03 [240v] •
- Control and Connection Box - ELPCB03N •
V12HB11040DA
- ELPFT01 - Finger Touch Unit •
V12H007A24
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx •
V12HA06A06
- ELPMB63 - Finger Touch Wall Bracket for •
ELPFT01
V12HA05A09
- External Speaker - ELPSP02 •
V12H467040

Wireless Presentation Systems

GENERAL	
Power consumption	W, 263 W (economy), 141 W (standby) 197
Product dimensions	mm x 395 mm x 133 mm (Width x Depth x Height) 356 V11HA78080 SKU
Supply Voltage	8715946715230 AC 100 V - 240 V, 50 Hz 60 Hz
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	% Operation 20 % - 80 %, Storage 10 % - 90
Options	مجموعة أسلاك السلامة
Loudspeaker	W 16
Room Type / Application	غرفة اجتماعات / قاعة دراسية
Positioning	تركيب في السقف، سطح المكتب، تركيب على الحائط
Colour	White

OTHER