

Epson EB-992F

DATASHEET / BROCHURE



EB-992F

Çok yönlü iş ekranı için ideal. Dahili kablosuz, Ekran Yansıtma ve 17.000 saatlik lamba ömrü ile 4.000 lümen Full HD projektör.

Bu Full HD projektörle içerik parlak, canlı ve net olur; herkesin derse katılmasını sağlar. 300 inç kadar ölçeklenebilir bu projektör, yüksek ortam aydınlatma koşullarında bile parlaktır. Bunu sağlayan, yüksek 4.000 lümen çıkış ve 16.000:1 kontrast oranıdır. Her çalışma ortamı farklıdır; bu nedenle kurulumu basit ve esnek bir projektöre ihtiyacınız vardır. Dahili kablosuz bağlantı, Ekran Yansıtma ve geniş bağlantı yelpazesi, çeşitli cihazlardan içerik paylaşımına olanak tanır. Eco modda 17.000 saate kadar lamba ömrü uzun süreli kesintisiz kullanım sağlar.

KEY FEATURES

- **Full HD parlak ve canlı kablosuz ekran**
3LCD teknolojisi ve eşit beyaz ve renkli ışık çıkışı
- **Minimum bakım**
Bakım gerekmeden yıllarca kesintisiz kullanım
- **Yayın ve paylaşım bağlantısı**
Dahili kablosuz bağlantı ve Ekran Yansıtma
- **Akıllı maliyet tasarrufu**
Eco modda 17.000 saate kadar lamba ömrü
- **Універсальне й гнучке керування**
Відтворення зображення з різних джерел через HDMI і додаткові можливості бездротового підключення

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-992F

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.61 inches with C2 Fine
IMAGE	
Color Light Output	4000 Lumens - 2400 Lumens (economy)
White Light Output	4000 Lumens - 2400 Lumens (economy)
Resolution	18p
High Definition	Full HD
Contrast Ratio	16,000
Light Source	Lamp
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.32 - 2.14:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	30 in - 300 in
Projection Lens F Number	1.99
Projection Lens Focal Length	29.2 mm
Projection Lens Focus	Manual
Offset	10 : 1
CONNECTIVITY	
Interfaces	Cinch audio in (1 x), USB 2. (1 x), USB 2.-A (1 x), Jack plug in (2 x), VGA out (1 x), Micro- phone input (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), RS-232C (1 x), HDMI in (2 x), Miracast (1 x), VGA in (2 x), Composite in (1 x), Jack plug out (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink
ADVANCED FEATURES	
Security	Kensington lock, Security cable hole, Wireless LAN security, Password protection, Control panel lock
Other Features	AV Mute Slide, Automatic keystone correction, Built-in speaker, Direct Power on/off, Docu- ment Camera Compatible, Easy OSD pre-setting, Horizontal and vertical keystone correc- tion, Network projection, OSD copy function, PC Free, Quick Corner, Split-Screen-Function, Wireless LAN capable, iProjection set-up by QR code, CEC compatible
Video Colour Modes	Blackboard, Cinema, Dynamic, Presentation, sRGB
Projector Control	AMX, Crestron, Control4, Extron

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	286 W, 327 W (economy), 180 W (standby)
Product dimensions	309 mm x 282 mm x 90 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection, Epson Projector Management
Noise Level	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wireless transmitter - ELPWT1
Loudspeaker	16 W
Room Type / Application	Huddle space / Portable, Meeting room / Classroom
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

Epson EB-992F

WHAT’S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- Warranty document
- HDMI Cable
- Quick Start Guide
- User Guide Kit (CD)

OPTIONAL ACCESSORIES

- Air Filter - ELPAF54
V13H134A54
- Ceiling Mount - ELPMB23 - White
V12H003B23
- Ceiling pipe - ELPFP13 - 668-918mm
V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
V12H003P14
- External Speaker - ELPSP02
V12H467040
- External Speaker - ELPSP02 - [240v]
- Lamp – ELPLP97 – EB9XX/W49/X/E20/U50/
EB-x05/x41/x42/EH-TW6
V13H010L97
- Safety Wire - ELPWR01
V12H003W01
- Soft Carry Case - ELPKS70
V12H001K70
- Wireless LAN Adapter - ELPAP11 (2.4GHz &
5GHz)
V12H005A01