Epson EB-L210SW

DATASHEET / BROCHURE



EB-L210SW

Best for classrooms and meeting rooms. Short-throw WXGA laser projector with 4,000 lumens and wireless connectivity.

The EB-L210SW's short throw lens allows close positioning of the projector to the display, ideal for small rooms and reducing the risk of shadows cast onto the display.Unlike some other brand projectors, EB-L210SW features 3LCD technology, enabling 4,000 lumens Colour and White Light Output levels for a bright and vibrant display. The experience is immersive and user-friendly. Scalable from 53-120", display sizes can be optimised for each room with one product and at a fixed cost, and produce a large display up-to 125", clearly visible from all angles and at a distance. The EB-L210SW can be portable, and there is no glass flat panel to create disruptive, reflected blind spots at certain angles.Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room. With USB 2A power output, HDMI streaming sticks can also be connected to open futher possibilities.

KEY FEATURES

- **Scalable, portable HD display**
  53-120" ST display for unrestricted viewing without reflections
- **Bright and energy efficient laser**
  4,000lm CLO with 3LCD technology for brighter colours at only 201W
- **Effortless connectivity options**
  Auto-on, wired / wireless display with USB 2A output for smart sticks
- **Simple to use and built to last**
  Virtually maintenance free with 5-year, 12,000hr warranty
- **Document camera compatibility**
  Create and record a live, totally immersive lesson or presentation

PRODUCT SPECIFICATIONS

Epson EB-L210SW

TECHNOLOGY	
Projection System	3LCD Technology Consists of LCD/Back lighting
LCD Panel	0.59 inches with C2 Fine
IMAGE	
Color Light Output	4000 Lumens - 2800 Lumens (economy)
White Light Output	4000 Lumens - 2800 Lumens (economy)
Resolution	WXGA 2
High Definition	HD ready
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 15, Manual horizontal: 15
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.48 - 0.65:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	55 in - 120 in
CONNECTIVITY	
Interfaces	Microphone input (1 x), Miracast (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), USB 2.0 Type B (Service Only) (1 x), VGA out (1 x), Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (1 x), RS-232C (1 x), HDMI in (2 x), USB 2.0 (1 x), Wi-Fi Direct (1 x), Jack plug in (2 x), VGA in (2 x), Jack plug out (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other Features	Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Instant on/off, Mail notification function, Microphone input, Network administration, Long light source life, OSD copy function, Quick Corner, Network projection, Split-Screen-Function, Set-up wizard, Screen Mirroring, Web Control, Web Remote, Wireless LAN capable, iProjection App
Video Colour Modes	Blackboard, Dynamic, Presentation, sRGB, Cinema
Projector Control	AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol, Crestron RoomView

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	201 W, 144 W (economy), 0.5 W (standby)
Heat Dissipation	884 BTUperhour
Product dimensions	325 mm x 337 mm x 90 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Management, EasyMP Multi PC Projection, Epson Projector Content Manager
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Visualiser camera, Wall mount, External Speaker, Ceiling mount
Loudspeaker	16 W
Room Type / Application	Meeting room / Classroom
Positioning	Wall Mounted, Table Mounted, Ceiling Mounted
Colour	White

OTHER

Epson EB-L210SW

WHAT'S IN THE BOX

- HDMI Cable 1.8m
- Quick Start Guide
- Remote control incl. batteries
- Power cable
- Warranty Documents

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  V13H134A60
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB03
- Control and Connection Box - ELPCB03 [240v]
  V12H927040DA
- Control and Connection Box - ELPCB03N
  V12HB11040DA
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]
  V12H467040DA
- Soft Carry Case - ELPKS71
  V12H001K71
- Wall Mount - ELPMB64 - EB-L2xx
  V12HA39010

EPSON®