

Epson EB-L720U

DATASHEET / BROCHURE



EB-L720U

Büyük toplantı alanları ve iş birliği için ideal. 4K destek ve kenar harmanlama ile 7.000 lümen WUXGA lazer ekran.

Güçlü 7.000 lümen yüksek parlaklık özelliği, Full HD, WUXGA, 16:6 geniş ekran, 4K giriş desteği ve detay geliştirme teknolojisi ile EB-L720U, 500 inçe kadar daha parlak, daha canlı ekranlar sunar. Bu ekran sınıfında genellikle beklenmeyecek daha fazla premium özellik sunan EB-L720U, tek bir kesintisiz büyük format ekran elde etmek için kenar harmanlama ve zengin geometrik düzeltme sağlar. Çoklu izleyici yapılandırmaları için ölçeklenebilir; piksel oluşumu, parlama, parmak izi ve geleneksel monitör çerçevelerinden arındırılmıştır.

KEY FEATURES

- **Yüksek parlaklık, ölçeklenebilir boyut**
500 inçe kadar 7.000 lümen yüksek parlaklıklı ekran sunar
- **Premium ekran özellikleri**
Full HD, 4K destek, kenar harmanlama ve geometrik düzeltme
- **Engelsiz görüş**
Piksel oluşumu, parlama, parmak izi ve merkezi çerçeveden arındırılmış
- **Sosyal mesafe desteği**
Ölçeklenebilir ekran her izleyici yapılandırmasının ihtiyaçlarını karşılar
- **Підключіть, натисніть і співпрацюйте**
Співпрацюйте за допомогою бездротової системи для презентацій Epson — ELPWP10

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-L720U

TECHNOLOGY

Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine

IMAGE

Color Light Output	7000 Lumens - 4900 Lumens (economy)
White Light Output	7000 Lumens - 4900 Lumens (economy)
Resolution	WUXGA
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual
Offset	27 : 1

CONNECTIVITY

Interfaces	USB 2. (1 x), RS-232C (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (Optional), Jack plug in (2 x), Ethernet Interface (1 Base-T/ 1-Base-TX/ 1-Base-T) (1 x), Jack plug out (1 x), USB 2.-A (1 x), HDMI in (2 x), HDBaseT (1 x), Miracast (Optional), VGA out (1 x), VGA in (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security	Kensington lock, Wireless LAN unit lock, Security cable hole, Padlock
Other Features	A/V mute, Arc Correction, Auto source search, Built-in speaker, Edge Blending, Home Screen, Instant on/off, Long light source life, PC Free, Power on button, Screen share, Split-Screen-Function, Ultra-wide display (16:6), iProjection App, CEC compatible, 21:9 aspect ratio support
Video Colour Modes	Dynamic, Cinema, Presentation, sRGB, DICOM SIM
Projector Control	AMX, Crestron, Control4, Crestron Integrated Partner, AMX Device Discovery, Control4 Simple Device Discovery Protocol, Extron IP Link, Extron XTP

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	287 W, 345 W (economy), 187 W (standby)
Product dimensions	440 mm x 122 mm x 304 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection
Noise Level	Normal: 39 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	HDBaseT Transmitter
Loudspeaker	10 W
Room Type / Application	Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Floor, Wall Mounted
Colour	White

OTHER

Epson EB-L720U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Power cable
- User guide
- Warranty Documents
- HDMI Cable
- Main unit

OPTIONAL ACCESSORIES

- Air Filter - ELPAF56 - L600/EB-14XX Series
V13H134A56
- Ceiling Mount - ELPMB22 - White
V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
V12H526040
- Ceiling Mount - ELPMB68
V12H006AE0
- Ceiling pipe - ELPFP13 - 668-918mm
V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
V12H003P14
- Extension Pole - ELPMB70 - For ELPMB68
V12H006AG0
- External Speaker - ELPSP02
V12H467040
- External Speaker - ELPSP02 - [240v]
- Portrait Adaptor - ELPMB69 - For ELPMB68
V12H006AF0