EB-L890E

DATASHEET / BROCHURE



EB-L890E

Ідеально для конференц-залів і лекційних аудиторій. Лазерний 3LCD-проєктор з покращенням 4K, широким зміщенням об’єктива та тихою роботою 26 дБ.

KEY FEATURES

Створюючи чіткі, яскраві зображення до 4,6 мільйона пікселів, цей бюджетний лазерний проєктор ідеально підходить для великих дисплеїв у професійних просторах.

- **Компактний дизайн з масштабованими зображеннями до 500”**

  Легкий дизайн, який спрощує транспортування та встановлення, забезпечуючи масштабовані зображення до 500” для високоякісної продуктивності в будь-якому середовищі.

- **Просте, гнучке встановлення**

  Фіксований центральний об’єктив із широким зміщенням і просунутими функціями встановлення забезпечує просте й адаптивне налаштування для будь-якого середовища.

- **Тиха робота**

  Забезпечує високопродуктивний дисплей з низьким рівнем шуму 26 дБ в Eco-режимі, гарантуючи тиху та зосереджену атмосферу для презентацій і зустрічей.

- **Making sustainable choices with Epson**

  Made from 19% recycled plastics, low power consumption, reduced packaging and a usage life of up to 30,000 hours in Eco mode (20,000 hours normal).

PRODUCT SPECIFICATIONS

EB-L890E

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	8000 Lumens - 5600 Lumens (economy)
White Light Output	8000 Lumens - 5600 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	RS-232C (1 x), USB 2.-A (2 x), HDMI (HDCP 2.3) (2 x), HDMI out (1 x), USB 2. Type B (Service Only) (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), Miracast (1 x), Jack plug out (1 x), HDBaseT (1 x), Near Field Communication (NFC) (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection
Other Features	21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App, Screen Mirroring
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT79
Projector Control	Crestron Integrated Partner, Extron XTP, AMX Device Discovery

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	388 W, 266 W (economy), 0.4 W (standby)
Product dimensions	440 mm x 340 mm x 138 mm (Width x Depth x Height)
Supply Voltage	AC 10 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 36 dB (A) - Economy: 26 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Air filter, Camera module, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP20
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User manual
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
  V13H134AF0
- Cable Cover - ELPCC07W-White - L6/7/89x Series
  V12H003AP0
- Camera Unit - ELPEC01
  V12HA46010
- Ceiling Mount - ELPMB22 - White
  V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
  V12H526040
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]

- Safety Wire - ELPWR01
  V12H003W01

EPSON®