EB-PQ2008W

DATASHEET / BROCHURE





EB-PQ2008W

Best for 4K installations and experiences. Compact 8,000-lumen 4K 3LCD laser projector with Crystal Motion technology.

Building on the success of the EB-PU Series, the EB-PQ2008W is not only small and light, but is highly affordable, versatile, energy-efficient and packed with advanced features. Allowing you the freedom to create unforgettable immersive experiences.Marvel at the clarity of the images produced by Epson's latest 4K technology. Combining its patented, state of the art 4K Crystal Motion and double micro-lens array technologies, Epson achieves a new benchmark in 4K image quality. Featuring a wide range of connectivity, including HDMI in/out supporting 120Hz 4K. This high brightness projector also benefits from cross-platform lens compatibility, using the same 4K lenses as the existing EB-PU Series, including the ELPLX02S zero-offset ultra-short throw lens which is perfect for immersive spaces. This projector is supplied 'body-only', allowing you to build the perfect solution for your installation. Built for exceptional reliability, the EB-PQ2008W is compatible with the ELPAF63 External Air Filter and provides up to 20,000 hours maintenance-free operation, or even longer in extended modes. Compatible with the ELPEC01 camera, Epson Projector Professional Tool and Epson Config Tool for a wealth of calibration, assistance and control functionality.

KEY FEATURES

- **Patented 4K and imaging technology**
  Outstanding 4K image quality delivers superb immersivity
- **Ultra-compact and lightweight**
  Small, powerful 8,000lm 4K projector
- **Cross-platform lens compatibility**
  Lets you build the optimal projection solution for every requirement
- **Fit-and-forget reliability**
  Up to 20,000 hours maintenance free
- **Reduced environmental impact**
  Energy-efficient with reduced requirements for packaging and transport

EPSON®

PRODUCT SPECIFICATIONS

EB-PQ2008W

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	1.04 inches with C2 Fine
IMAGE	
Color Light Output	8000 Lumens - 5600 Lumens (economy)
White Light Output	8000 Lumens - 5600 Lumens (economy)
Resolution	4K 3840 x 2160, 8.3m pixels, 16:9
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 45
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.34 - 7.16:1
Lens	Optical
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	Near Field Communication (NFC) (1 x), Jack plug out (1 x), USB 2.0 Type B (Service Only) (1 x), USB content playback (1 x), Remote (1 x), Wireless LAN IEEE 802.11a/b/g/n (Optional), HDMI in (2 x), HDMI out (1 x), HDBaseT (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0-A (2 x), RS-232C (1 x)
Network Protocol	HTTPS, SNMP, PJLink, IPv6, ESC/VP.net
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Password protection, Wireless LAN security, Padlock, Wireless LAN unit lock
Other Features	21:9 aspect ratio support, A/V mute, Auto Power On, Direct Power on/off, Edge Blending, Frame interpolation, Freeze image, Horizontal and vertical keystone correction, Lens position memory, Long light source life, Point correction, OSD copy function, Quick Corner, Schedule Function, Web Control, Wireless LAN capable, Auto source search, iProjection App
Video Colour Modes	Dynamic, Natural, Presentation, BT709, Multi Projection, DICOM SIM, Cinema
Projector Control	Extron XTP, AMX Device Discovery, Crestron Integrated Partner, Extron IP Link

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Heat Dissipation	1,707 BTUperhour
Product dimensions	545 mm x 436 mm x 189 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Creative Projection, Epson Projector Config Tool, Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool
Noise Level	Normal: 35 dB (A) - Economy: 29 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Air filter, Camera module, Wireless LAN unit, Ceiling mount
Room Type / Application	Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction, Boardroom
Positioning	Ceiling Mounted, Desktop, Floor, Flying Frame, Table Mounted, Wall Mounted
Colour	White

OTHER

EB-PQ2008W

WHAT'S IN THE BOX

- Cable cover
- Lens connector cap
- Main unit
- Power cable
- Remote control incl. batteries
- Document Pack
- Information sheet
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF46 - EB-L107x/-Z9xxx/ Z1000xU/Z11xxx
- Camera Unit - ELPEC01
- Ceiling Mount - ELPMB68
- External Air Filter - ELPAF63 - EB-PU1000 Series
- Lens - ELPLL08 - Long throw - EB-PU Series
- Lens - ELPLM10 - Mid throw 3 - EB-PU Series
- Lens - ELPLM11 - Mid throw 4 - EB-PU Series
- Lens - ELPLM15 - Mid throw - EB-PU Series
- Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
- Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series

EPSON®