


Epson EB-L210SF

DATASHEET / BROCHURE



EB-L210SF

Best for meeting rooms. Short-throw Full HD laser projector with 4,000 lumens and wireless connectivity.

The EB-L210SF's short throw lens allows close positioning of the projector to the display, ideal for small rooms and reducing the risk of shadows cast onto the display. Unlike some other brand projectors, EB-L210SF features 3LCD technology, enabling 4,000 lumens for a bright and vibrant display. The experience is immersive and user-friendly. Scalable from 55-125", display sizes can be optimised for each room with one product and a fixed cost, and it supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image. With up-to 30,000 hour long-life laser-light source, it produces a large display up-to 125", clearly visible from all angles and at a distance, and unlike a flat-panel display, the EB-L210SF can be portable, and there is no glass flat panel to create disruptive, reflected blind spots at certain angles. Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room. With USB 2A power output, HDMI streaming sticks can also be connected to open further possibilities.

KEY FEATURES

- **Scalable, portable FHD display**
55-125" ST display for unrestricted viewing without reflections
- **Bright and energy efficient laser**
4,000lm CLO with 3LCD technology for brighter colours at only 201W
- **Effortless connectivity options**
Auto-on, wired / wireless display with USB 2A output for smart sticks
- **Simple to use and built to last**
Virtually maintenance free with 5-year, 12,000hr warranty
- **Document camera compatibility**
Create and record a live, totally immersive lesson or presentation

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-L210SF

TECHNOLOGY

Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.62 inches with C2 Fine

IMAGE

Color Light Output	4000 Lumens - 2800 Lumens (economy)
White Light Output	4000 Lumens - 2800 Lumens (economy)
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 15, Manual horizontal: 15
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	0.45 - 0.61:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	55 in - 125 in
Projection Lens Focus	Manual
Offset	11 : 1

CONNECTIVITY

Interfaces	RS-232C (1 x), VGA out (1 x), Jack plug in (2 x), Microphone input (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), Jack plug out (1 x), Miracast (1 x), VGA in (2 x), Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (1 x), USB 2.0 Type B (Service Only) (1 x), Wi-Fi Direct (1 x), HDMI in (2 x), USB 2.0 (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other Features	Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Easy OSD pre-setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Instant on/off, Mail notification function, Microphone input, Network administration, Long light source life, OSD copy function, Quick Corner, Network projection, Split-Screen-Function, Set-up wizard, Screen Mirroring, Web Control, Web Remote, Wireless LAN capable, iProjection App
Video Colour Modes	Blackboard, Dynamic, Presentation, sRGB, DICOM SIM, Cinema, Multi Projection
Projector Control	AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Extron IP Link, Crestron RoomView, AMX Device Discovery, Extron XTP, Control4 Simple Device Discovery Protocol

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	201 W, 260 W (economy), 144 W (standby)
Heat Dissipation	884 BTUperhour
Product dimensions	325 mm x 337 mm x 90 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Management, Epson Projector Content Manager, EasyMP Multi PC Projection
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Visualiser camera, Wall mount, Ceiling mount, External Speaker
Loudspeaker	16 W
Room Type / Application	Meeting room / Classroom, Boardroom
Positioning	Ceiling Mounted, Wall Mounted, Table Mounted
Colour	White

OTHER

Epson EB-L210SF

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- HDMI Cable 1.8m
- Quick Start Guide
- Warranty Documents

OPTIONAL ACCESSORIES

- Air Filter - ELP AF60 - EB-7XX / EB-L2xx Series V13H134A60
- Ceiling pipe - ELPFP13 - 668-918mm V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm V12H003P14
- Control and Connection Box - ELPCB03

- Control and Connection Box - ELPCB03 [240v] V12H927040DA
- Control and Connection Box - ELPCB03N V12HB11040
- External Speaker - ELPSP02 V12H467040
- External Speaker - ELPSP02 - [240v] V12H467040DA
- Soft Carry Case - ELPKS71 V12H001K71
- Wall Mount - ELPMB64 - EB-L2xx V12HA39010