EB-L790U

DATASHEET / BROCHURE



EB-L790U

Best for meeting rooms and lecture halls. WUXGA 3LCD laser projector with wide lens shift and quiet operation.

KEY FEATURES

Ideal for meeting rooms, lecture halls and more. This compact, budget-friendly laser display delivers high-quality performance in any setting.

- **Compact design with scalable images up to 500”**

  The lightweight design simplifies transport and installation while offering scalable images up to 500” for maximum flexibility.

- **Effortless, flexible installation**

  With a fixed centre lens display, wide lens shift, and advanced features, setup is easy and adaptable to any environment.

- **Quiet operation**

  A high-performance projector with a low noise level of 25dB in Eco mode, ensuring a quiet, focused environment for presentations and meetings.

- **Making sustainable choices with Epson**

  Made from 19% recycled plastics, low power consumption, reduced packaging and a usage life of up to 30,000 hours in eco mode (20,000 hours normal).

EPSON®

PRODUCT SPECIFICATIONS

EB-L790U

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	7300 Lumens - 5110 Lumens (economy)
White Light Output	7300 Lumens - 5110 Lumens (economy)
Resolution	WUXGA
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	Near Field Communication (NFC) (1 x), RS-232C (1 x), Miracast (1 x), USB 2.0 (2 x), HDMI (HDCP 2.3) (2 x), HDMI out (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), HDBaseT (1 x), Jack plug out (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0 Type B (Service Only) (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection
Other Features	21:9 aspect ratio support, A/V mute, Auto Power On, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App, Screen Mirroring
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT709
Projector Control	Crestron Integrated Partner, Extron XTP, AMX Device Discovery

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	388 W, 0.4 W (economy), 0.4 W (standby)
Heat Dissipation	1,598 BTUperhour
Product dimensions	440 mm x 340 mm x 138 mm (Width x Depth x Height)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 36 dB (A) - Economy: 26 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Air filter, Camera module, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, WP System - ELPWP20
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User guide
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
- Cable Cover - ELPCC07W-White - L6/7/89x Series
- Camera Unit - ELPEC01
- Ceiling Mount - ELPMB22 - White
- Ceiling Mount - ELPMB30 - Low profile
- Ceiling pipe - ELPFP13 - 668-918mm
- Ceiling pipe - ELPFP14 - 918-1168mm
- External Speaker - ELPSP02
- External Speaker - ELPSP02 - [240v]
- Safety Wire - ELPWR01

EPSON®