

EB-L735U

DATASHEET / BROCHURE



EB-L735U

Лазерний проєктор із фіксованим об'єктивом EB-L735U підтримує яскравість у 7000 люменів та ідеально підійде для навчальних закладів, корпоративного сектору, роздрібних магазинів і реклами.

Яскрава та економна проєкційна системаПроектор EB-L735U відтворює виразніше, яскравіше та захопливіше зображення з неймовірною яскравістю 7000 люменів у роздільній здатності WUXGA Full HD — і все це за доступною ціною. Для користувачів це відкриває можливість перейти на новий рівень надійності й продуктивності їхньої лазерної проєкційної системи з меншими енергоспоживанням і без надлишкових витрат. Додатково вони отримують: підтримку 4K, технологію покращення деталей, безшовна мултипроєкція та систему зсуву об'єктива для встановлення в складних конструкціях. Модель EB-L735U може працювати з екранами діагоналю до 500 дюймів без зменшення чіткості зображення й передачі деталей. Розширені можливості підключенняЦя проєкційна система може підключатися різними способами та показувати зображення з кількохджерел одночасно включно з бездротовою передачею. Модель EB-L735U оснащено передовими можливостями підключення, серед яких HDMI та HDBaseT з підтримкою сигналу 4K, бездротовий стандарт 5 ГГц із корпоративним рівнем захисту, покращена технологія Miracast, вбудований мультимедійний програвач і підтримка бездротової системи презентування ELPWP10 від Epson. Простота й гнучкість установкиЦей стильний і компактний проєктор можна встановлювати в будь-якому напрямку без втрати якості зображення, він підтримує роботу з ультраширокими екранами 16:6, HDMI та безшовну мултипроєкцію для систем із кількох проєкторів. Також доступний у білому кольорі.

KEY FEATURES

- **Яскравість 7000 люменів**
Чіткі зображення та яскраві кольори навіть у гарно освітлених приміщеннях
- **Роздільна здатність WUXGA**
Чітке зображення Full HD для відмінної деталізації
- **Передові варіанти підключення**
Підтримка сигналу 4K, HDMI, HDBaseT, вбудований Wi-Fi та дублювання екрана
- **Простота й гнучкість установки**
Легкий і компактний проєктор із системою зсуву об'єктива
- **Підтримка соціального дистанціювання**
Масштабований дисплей розміром до 500 дюймів

PRODUCT SPECIFICATIONS

EB-L735U

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine

IMAGE	
Color Light Output	7000 Lumens - 4900 Lumens (economy)
White Light Output	7000 Lumens - 4900 Lumens (economy)
Resolution	WUXGA
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours

OPTICAL	
Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual

CONNECTIVITY	
Interfaces	USB 2. (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), RS-232C (1 x), USB 2 Type A playback (1 x), USB 2.-A (1 x), HDMI (HDCP 2.3) (2 x), VGA out (1 x), HDBaseT (1 x), Miracast (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), Jack plug out (1 x), VGA in (2 x), Wireless LAN a/n (5GHz) (1 x), HDMI out (1 x), Jack plug in (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	IPv6, ESC/VP.net, PJLink, SNMP, HTTPS

ADVANCED FEATURES	
Security	Kensington lock, Wireless LAN unit lock, Control panel lock, Security cable hole, Wireless LAN security, Password protection
Other Features	A/V mute, Arc Correction, Auto Power On, Auto source search, Built-in speaker, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, JPEG Viewer, Long light source life, PC Free, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Super resolution, Ultra-wide display (16:6), Volume control, Web Control, Web Remote, Wireless LAN capable, iProjection App, CEC compatible, 21:9 aspect ratio support
Video Colour Modes	Dynamic, Cinema, sRGB, Presentation, DICOM SIM, Multi Projection
Projector Control	AMX Device Discovery, Control4 Simple Device Discovery Protocol, Extron XTP, Extron IP Link, Crestron Integrated Partner

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	287 W, 345 W (economy), 187 W (standby)
Product dimensions	440 mm x 339 mm x 136 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 38 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Document camera, HDBaseT Transmitter, Wireless LAN unit, External Speaker, MB22 ceiling mount
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	Black

OTHER

EB-L735U

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- User guide
- Warranty Documents
- Main unit
- HDMI Cable

OPTIONAL ACCESSORIES

- Air Filter - ELPAF56 - L600/EB-14XX Series
V13H134A56
- Ceiling Mount - ELPMB22 - White
V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
V12H526040
- Ceiling Mount - ELPMB68
V12H006AE0
- Ceiling pipe - ELPFP13 - 668-918mm
V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
V12H003P14
- Extension Pole - ELPMB70 - For ELPMB68
V12H006AG0
- Portrait Adaptor - ELPMB69 - For ELPMB68
V12H006AF0
- Safety Wire - ELPWR01
V12H003W01
- Truss Adaptor - ELPMB71 - For ELPMB68
V12H006AH0

