



EB-L690U

Best for meeting rooms and lecture halls. WUXGA 3LCD laser projector with wide lens shift and quiet operation.

KEY FEATURES

Ideal for meeting rooms, lecture halls and more. This compact, budget-friendly laser projector delivers high-quality performance in any setting.

- **Compact design with scalable images up to 500"**

The lightweight design simplifies transport and installation while offering scalable images up to 500" for maximum flexibility.

- **Effortless, flexible installation**

With a fixed centre lens display, wide lens shift, and advanced features, setup is easy and adaptable to any environment.

- **Quiet operation**

Enjoy high-performance projector with a low noise level of 25dB in Eco mode, ensuring a quiet, focused environment for presentations and meetings.

- **Making sustainable choices with Epson**

Made from 19% recycled plastics, low power consumption, reduced packaging and a usage life of up to 30,000 hours in eco mode (20,000 hours normal).

PRODUCT SPECIFICATIONS

EB-L690U

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	6500 Lumens - 4550 Lumens (economy)
White Light Output	6500 Lumens - 4550 Lumens (economy)
Resolution	WUXGA
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.35 - 2.2:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	50 in - 500 in
Projection Lens F Number	1.7
Projection Lens Focal Length	31.8 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	RS-232C (1 x), USB 2.0 Type B (Service Only) (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), USB 2.0-A (2 x), Near Field Communication (NFC) (1 x), HDMI (HDCP 2.3) (2 x), HDMI out (1 x), HDBaseT (1 x), Miracast (1 x), Jack plug out (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	SNMP, HTTPS, PJLink, ESC/VP.net
ADVANCED FEATURES	
Security	Padlock, Security cable hole, Kensington lock, Wireless LAN unit lock, Password protection, Control panel lock
Other Features	21:9 aspect ratio support, A/V mute, Auto Power On, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App, Screen Mirroring
Video Colour Modes	Dynamic, Presentation, Cinema, BT709, Natural, DICOM SIM, Multi Projection
Projector Control	Extron XTP, AMX Device Discovery, Crestron Integrated Partner

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	336 W, 233 W (economy), 0.4 W (standby)
Product dimensions	440 mm x 340 mm x 138 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 32 dB (A) - Economy: 25 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Suspension adapter
Loudspeaker	10 W
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

EB-L690U

WHAT’S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User guide
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
V13H134AF0
- Cable Cover - ELPCC07W-White - L6/7/89x Series
V12H003AP0
- Camera Unit - ELPEC01
V12HA46010
- Ceiling Mount - ELPMB22 - White
V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
V12H526040
- Ceiling pipe - ELPFP13 - 668-918mm
V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
V12H003P14
- External Speaker - ELPSP02
V12H467040
- External Speaker - ELPSP02 - [240v]
V12H467040DA
- Safety Wire - ELPWR01
V12H003W01