

# Epson L6490 CIS



## EcoTank Business+ L6490

**Best for demanding businesses that need ultra-fast colour 4-in-1 performance with high-capacity ink.**

Get more done in less time.

Take your business printing to the next level with this ultra-fast and efficient printer that can deliver a first page in as little as 7 seconds\*. Feature-rich A4 EcoTank.

Print, copy, scan and fax with the L6490 which features double-sided printing, a 250-sheet front paper tray and 35-page automatic document feeder. It's easy to navigate the extensive range of features with the 6.1cm LCD touch-screen.

Keep on saving.

Making a saving every time you print with this EcoTank that delivers an incredibly low cost-per-page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

Business-quality printing.

The fast drying EcoTank 112 ink series features all pigment inks for smudge, water and highlighter resistant prints. From one set of replacement inks, you can produce up to 7,500 pages in black and 6,000 in colour\*\*

Print from almost anywhere.

With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint and Smart Panel apps\*\*\*. Easy to use and reliable.

Filling the ink tanks is simple with the resealable, intuitive and mess-free ink bottles. Epson's unique Heat-Free PrecisionCore Technology offers improved reliability, reduced downtime and less environmental impact. No warm up time means the first page prints fast uses less power.

## KEY FEATURES

- **Ultra-fast print speeds**  
Up to 17ipm\*\*\*\*
- **Ultra-low-cost per page**  
Economical ink tank system
- **Easy to use front ink tank**  
Enjoy hassle-free refills with enhanced ink bottles
- **Mobile printing and connectivity**  
Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps\*\*\*
- **Designed for business**  
A4 multifunction printer with fax, 250-sheet front tray, 35-sheet ADF

## PRODUCT SPECIFICATIONS

### TECHNOLOGY

Printing Method	PrecisionCore™ Print Head
Minimum Droplet Size	3.3 pl, With Variable-Sized Droplet Technology
Ink Technology	Pigment ink
Printing Resolution	4800 x 1200 DPI

### PRINT

Printing Speed ISO/IEC 24734	17 Pages/min Monochrome, 9.5 Pages/min Colour
------------------------------	---

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

### SCAN

Scanner Type	Contact image sensor (CIS)
--------------	----------------------------

### PAPER / MEDIA HANDLING

Paper Formats	User defined
Duplex	Yes
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.)
Media Handling	Automatic duplex (A4, plain paper)

### GENERAL

Product dimensions	346 mm x 375 mm x 347 mm (Width x Depth x Height)
Noise Level	5.1 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 38 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode
Compatible Operating Systems	Windows 8.1, Windows 8, Mac OS X 10.6.8 or later, Windows 7, Windows Vista, Windows XP, XP Professional x64 Edition, Windows 10
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)
Mobile and Cloud Printing Services	Apple AirPrint, Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud)

### OTHER FEATURES

Panel	Type: Colour, Diagonal: 6.1
Features	Touchscreen

### OTHER

## LOGISTICS INFORMATION

SKU	C11CJ88405
EAN Code	8715946689234
Country Of Origin	Philippines

## Epson L6490 CIS

### WHAT'S IN THE BOX

- Warranty document
- Main unit
- Power cable
- Setup guide
- 1 set of ink (1x 127ml BK, 3x 70ml cmY) + Extra Black
- Driver and utilities (CD)

### INK COMPATIBILITY

- 112 EcoTank Pigment Black ink bottle
- 112 EcoTank Pigment Cyan ink bottle
- 112 EcoTank Pigment Magenta ink bottle
- 112 EcoTank Pigment Yellow ink bottle
- XP-5100 / WF-2860DWF / ET-3700 / ET-4750 / L6000 / ET-15000 Series Maintenance Box

### INK YIELD DATA

Included	* 13,300 Pages	* 5,200 Pages
----------	----------------	---------------

### Replacement

\* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower.

1 First-Print-Out-Time (FPOT) measurement method: ISO/IEC17629 Office Category Test; paper size A4. A set of Microsoft Word, Microsoft Excel and PDF files (each set containing 4 pages) is continuously printed. Measurement is based on the average time for the first of the four single-sided prints to exit the printer. Measurement starts when the print button is pressed and ends when the first page of the set exits. 2 Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 based on the replacement ink bottles. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower. 3 Requires a wireless connection to the internet. For more information, supported languages and devices please visit [www.epsonconnect.eu4](http://www.epsonconnect.eu4) Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit [www.epson.eu/testing](http://www.epson.eu/testing)

**EPSON®**