Epson EB-L210SF

DATASHEET / BROCHURE



EB-L210SF

Ідеально для конференц-залів. Короткофокусний лазерний проєктор Full HD з 4000 люменами та бездротовим підключенням.

Короткофокусний об'єктив EB-L210SF дозволяє близьке розміщення проєктора до дисплея, ідеально для невеликих кімнат і зниження ризику тіней на дисплеї. На відміну від проєкторів деяких інших брендів, EB-L210SF має технологію 3LCD, що забезпечує 4000 люменів для яскравого та насиченого дисплея. Враження занурювальне та зручне для користувача. Масштабований від 55 до 125", розміри дисплея можна оптимізувати для кожної кімнати з одним продуктом і фіксованою вартістю, а також підтримує мультипроєкторне зрощення країв для недорогого, великого, безшовного, енергоефективного зображення 3780x1080p. З довговічним лазерним джерелом світла до 30 000 годин він створює великий дисплей до 125", чітко видимий з усіх кутів і на відстані. На відміну від плоскопанельного дисплея, EB-L210SF може бути портативним, а тут немає скляної плоскої панелі, яка створює відбиваючі сліпі плями під певними кутами. Універсальні варіанти дротового та бездротового підключення, зокрема дзеркалювання екрана Miracast™, забезпечують безпроблемний обмін контентом між кількома пристроями, а з підключеним опціональним візуалізатором Epson документи, презентації або 3D-об'єкти можна проєціювати з неймовірною деталізацією для всієї кімнати. З виходом USB 2A потужності також можна підключати HDMI-стрімінгові стики, щоб відкрити подальші можливості.

KEY FEATURES

- **Масштабований, портативний FHD дисплей**

  55–125" короткофокусний дисплей для безперешкодного перегляду без відблисків

- **Яскравий і енергоефективний лазер**

  4000 лм CLO з технологією 3LCD для яскравіших кольорів при лише 201 Вт

- **Прості варіанти підключення**

  Авто-ввімкнення, дротовий/ бездротовий дисплей із USB 2A виходом для смарт-стиків

- **Простий у використанні та створений довго служити**

  Практично безобслуговувальний із 5-річною гарантією на 12 000 годин

- **Сумісність із документ-камерою**

  Створюйте та записуйте живі уроки або презентації з ефектом присутності

PRODUCT SPECIFICATIONS

Epson EB-L210SF

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.62 inches with C2 Fine
IMAGE	
Color Light Output	4000 Lumens - 2800 Lumens (economy)
White Light Output	4000 Lumens - 2800 Lumens (economy)
Resolution	18p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 15, Manual horizontal: 15
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.45 - 0.61:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	55 in - 300 in
Projection Lens Focus	Manual
Offset	11 : 1
CONNECTIVITY	
Interfaces	USB 2. (1 x), Microphone input (1 x), Wi-Fi Direct (1 x), Miracast (1 x), USB 2. Type B (Service Only) (1 x), Wireless LAN IEEE 82.11a/b/g/n/ac (1 x), HDMI in (2 x), Ethernet Interface (1 Base-T/ 1-Base TX/ 1-Base-T) (1 x), VGA out (1 x), Jack plug in (2 x), VGA in (2 x), RS-232C (1 x), Jack plug out (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection
Other Features	Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Easy OSD pre-setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Instant on/off, Mail notification function, Microphone input, Network administration, Long light source life, OSD copy function, Quick Corner, Network projection, Split-Screen-Function, Set-up wizard, Screen Mirroring, Web Control, Web Remote, Wireless LAN capable, iProjection App
Video Colour Modes	Blackboard, Dynamic, Presentation, sRGB, DICOM SIM, Cinema, Multi Projection
Projector Control	AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Extron IP Link, Crestron RoomView, AMX Device Discovery, Extron XTP, Control4 Simple Device Discovery Protocol

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	201 W, 144 W (economy), 0.5 W (standby)
Product dimensions	325 mm x 337 mm x 90 mm (Width x Depth x Height)
Heat Dissipation	884 BTUperhour
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Management, Epson Projector Content Manager, EasyMP Multi PC Projection
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Connection and control box, Visualiser camera, Wall mount, Ceiling mount, External Speaker
Loudspeaker	16 W
Room Type / Application	Meeting room / Classroom, Boardroom
Positioning	Ceiling Mounted, Wall Mounted, Table Mounted
Colour	White

OTHER

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- HDMI Cable 1.8m
- Quick Start Guide
- Warranty Documents

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  V13H134A60
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB03
  V12H927040
- Control and Connection Box - ELPCB03 [240v]

- Control and Connection Box - ELPCB03N
  V12HB11040
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]

- Soft Carry Case - ELPKS71
  V12H001K71
- Wall Mount - ELPMB64 - EB-L2xx
  V12HA39010

EPSON®