# Epson EB-L210SF

## DATASHEET / BROCHURE




EB-L210SF

**Best for meeting rooms. Short-throw Full HD laser projector with 4,000 lumens and wireless connectivity.**

The EB-L210SF's short throw lens allows close positioning of the projector to the display, ideal for small rooms and reducing the risk of shadows cast onto the display unlike some other brand projectors, EB-L210SF features 3LCD technology, enabling 4,000 lumens for a bright and vibrant display. The experience is immersive and user-friendly. Scalable from 300", display sizes can be optimised for each room with one product and a fixed cost, and it supports multi-projection edge-blending for a low cost, large, seamless, energy efficient 3780x1080p image. With up-to 30,000 hour long-life laser-light source, it produces a large display up-to 300", clearly visible from all angles and at a distance, and unlike a flat-panel display, the EB-L210SF can be portable, and there is no glass flat panel to create disruptive, reflected blind spots at certain angles. Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensures effortless, multi-device content sharing, and with a connected optional Epson visualiser, documents, presentations or 3D objects can be projected in incredible detail to the whole room. With USB 2A power output, HDMI streaming sticks can also be connected to open further possibilities.

## KEY FEATURES

- **Scalable, portable FHD display**
  300" ST display for unrestricted viewing without reflections
- **Bright and energy efficient laser**
  4,000lm CLO with 3LCD technology for brighter colours at only 201W
- **Effortless connectivity options**
  Auto-on, wired / wireless display with USB 2A output for smart sticks
- **Simple to use and built to last**
  Virtually maintenance free with 5-year, 12,000hr warranty
- **Document camera compatibility**
  Create and record a live, totally immersive lesson or presentation

# PRODUCT SPECIFICATIONS

Epson EB-L210SF

| | |
|---|---|
| **TECHNOLOGY** | |
| Projection System | 3LCD Technology<br>RGB liquid crystal shutter |
| LCD Panel | 0.62 inches with C2 Fine |
| **IMAGE** | |
| Color Light Output | 4000 Lumens - 2800 Lumens (economy) |
| White Light Output | 4000 Lumens - 2800 Lumens (economy) |
| Resolution | 1080p |
| High Definition | Full HD |
| Contrast Ratio | 5,000,000 |
| Light Source | Laser |
| Laser Light source | 20000 hr Durability High, 30000 hr Durability Eco |
| Keystone Correction | Manual vertical: 15, Manual horizontal: 15 |
| Colour Video Processing | 10 Bits Color |
| Colour Reproduction | Upto 1.07 billion colours |
| **OPTICAL** | |
| Throw Ratio | 0.45 - 0.61:1 |
| Zoom | Digital, Factor: 1 - 1.35 |
| Lens | Optical |
| Screen Size | 55 in - 300 in |
| Projection Lens Focus | Manual |
| Offset | 11 : 1 |
| **CONNECTIVITY** | |
| Interfaces | Jack plug in (2 x), Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T) (1 x), Jack plug out (1 x), RS-232C (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), Miracast (1 x), Microphone input (1 x), USB 2.0 Type B (Service Only) (1 x), Wi-Fi Direct (1 x), HDMI in (2 x), USB 2.0 (1 x), VGA in (2 x), VGA out (1 x) |
| Epson iProjection App | Ad-Hoc / Infrastructure |
| Network Protocol | HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink |
| **ADVANCED FEATURES** | |
| Security | Kensington lock, Control panel lock, Password lock, Padlock, Security cable hole, Wireless LAN unit lock, Wireless LAN security, Password protection |
| Other Features | Arc Correction, Auto Power On, Auto source search, Built-in speaker, CEC compatible, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Easy OSD pre-setting, Email notification, Home Screen, Horizontal and vertical keystone correction, Instant on/off, Mail notification function, Microphone input, Network administration, Long light source life, OSD copy function, Quick Corner, Network projection, Split-Screen-Function, Set-up wizard, Screen Mirroring, Web Control, Web Remote, Wireless LAN capable, iProjection App |
| Video Colour Modes | Blackboard, Dynamic, Presentation, sRGB, DICOM SIM, Cinema, Multi Projection |
| Projector Control | AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Extron IP Link, Crestron RoomView, AMX Device Discovery, Extron XTP, Control4 Simple Device Discovery Protocol |

EPSON®

## PRODUCT SPECIFICATIONS

| GENERAL | |
|---|---|
| Power consumption | 201 W, 144 W (economy), 0.5 W (standby) |
| Heat Dissipation | 884 BTUperhour |
| Product dimensions | 325 mm x 337 mm x 90 mm (Width x Depth x Height) |
| Supply Voltage | AC 100 V - 240 V, 50 Hz - 60 Hz |
| Included Software | Epson Projector Management, Epson Projector Content Manager, EasyMP Multi PC Projection |
| Noise Level | Normal: 37 dB (A) - Economy: 27 dB (A) |
| Supported Temperature | Storage -10 °C - 60 °C |
| Supported Humidity | Operation 20 % - 80 %, Storage 10 % - 90 % |
| Options | Connection and control box, Visualiser camera, Wall mount, Ceiling mount, External Speaker |
| Loudspeaker | 16 W |
| Room Type / Application | Meeting room / Classroom, Boardroom |
| Positioning | Ceiling Mounted, Wall Mounted, Table Mounted |
| Colour | White |

**OTHER**

Epson EB-L210SF

## WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- HDMI Cable 1.8m
- Quick Start Guide
- Warranty Documents

## OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  V13H134A60
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB03
  V12H927040
- Control and Connection Box - ELPCB03 [240v]

- Control and Connection Box - ELPCB03N
  V12HB11040
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]

- Soft Carry Case - ELPKS71
  V12H001K71
- Wall Mount - ELPMB64 - EB-L2xx
  V12HA39010

EPSON®