

Epson EB-982W

DATASHEET / BROCHURE



EB-982W

Можливість установлення майже в будь-якому місці поєднується з відмінною яскравістю й чіткістю, а також із продуктивною роботою без потреби в частому технічному обслуговуванні.

{bЯскравий, насичений контент на великому масштабованому екрані} Насолоджуйтеся презентаціями у великому форматі з чітким, контрастним текстом, привабливим зображенням і відеоконтентом на екранах розміром до 300 дюймів. Яскравість 3600 люменів і високий коефіцієнт контрастності 16 000:1 забезпечують надзвичайну візуальну продуктивність навіть у добре освітлених приміщеннях. {bРоки конференцій без простоїв} Завдяки лампі з тривалістю експлуатації до 12 000 годин у режимі Eco. {bГнучкі можливості встановлення й розташування} Автоматична вертикальна й горизонтальна корекція кутових спотворень забезпечує гнучкість розташування проектора в приміщеннях і гарантує зображення без деформацій, а широкоформатне оптичне збільшення надає ще більше можливостей роботи. {bМережеве й бездротове з'єднання (додатково)} Підключення до мережі (за протоколом RJ45) і додаткові можливості бездротового підключення дозволяють приєднувати EB-X49 до корпоративної мережі або пізніше оновити до бездротового доступу до пристроїв. {bВисокоякісний звук} У цей проектор вбудовано динамік 5 Вт, завдяки якому аудіоконтент лунає чітко й не потрібні додаткові зовнішні динаміки.

KEY FEATURES

- **Високоякісне яскраве зображення**

Технологія 3LCD й однаково високі яскравість білого кольору та колірна яскравість

- **Портативність**

Невеликі розмір і вага дозволяють легко переносити проектор і користуватися ним у різних приміщеннях

- **Широкий вибір варіантів підключення**

Можливості мережевого й бездротового зв'язку

- **Низька загальна вартість володіння**

До 12 000 годин експлуатації лампи в режимі Eco

- **Універсальне й гнучке керування**

Відтворення зображення з різних джерел через HDMI і додаткові можливості бездротового підключення

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-982W

TECHNOLOGY

Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.59 inches with MLA (D9)

IMAGE

Color Light Output	4200 Lumens - 2600 Lumens (economy)
White Light Output	4200 Lumens - 2600 Lumens (economy)
Resolution	WXGA 2
High Definition	HD ready
Light Source	Lamp
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours

OPTICAL

Throw Ratio	1.38 - 2.24:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	29 in - 280 in
Projection Lens F Number	1.99
Projection Lens Focal Length	29.2 mm
Offset	10 : 1

CONNECTIVITY

Interfaces	HDMI in (2 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), USB 2. (1 x), VGA in (2 x), Composite in (1 x), Jack plug in (2 x), VGA out (1 x), USB 2.-A (1 x), RS-232C (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (Optional), Cinch audio out (1 x), Jack plug out (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink

ADVANCED FEATURES

Security	Kensington lock, Security cable hole, Wireless LAN unit lock, Password protection, Control panel lock
Other Features	AV Mute Slide, Automatic keystone correction, Built-in speaker, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Horizontal and vertical keystone correction, Network projection, OSD copy function, PC Free, Quick Corner, Split-Screen-Function, Wireless LAN capable, iProjection set-up by QR code, CEC compatible
Video Colour Modes	Blackboard, Cinema, Dynamic, Sports, sRGB
Projector Control	AMX, Crestron, Control4, Extron

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	286 W, 327 W (economy), 180 W (standby)
Product dimensions	309 mm x 282 mm x 90 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection, Epson Projector Management
Noise Level	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Spare lamp
Loudspeaker	16 W
Room Type / Application	Meeting room / Classroom, Large Meeting Room / Auditorium, Huddle space / Portable, Boardroom
Positioning	Ceiling Mounted, Desktop
Colour	White

OTHER

Epson EB-982W

WHAT'S IN THE BOX

- Main unit
- Remote control incl. batteries
- Power cable
- HDMI Cable
- Quick Start Guide
- Warranty document
- User Guide Kit (CD)

OPTIONAL ACCESSORIES

- Air Filter - ELPAF54
V13H134A54
- Ceiling Mount - ELPMB23 - White
V12H003B23
- Ceiling pipe - ELPPFP13 - 668-918mm
V12H003P13
- Ceiling pipe - ELPPFP14 - 918-1168mm
V12H003P14
- External Speaker - ELPSP02
V12H467040
- External Speaker - ELPSP02 - [240v]

- Lamp – ELPLP97 – EB9XX/W49/X/E20/U50/
EB-x05/x41/x42/EH-TW6
V13H010L97
- Safety Wire - ELPWR01
V12H003W01
- Soft Carry Case - ELPKS70
V12H001K70
- Wireless LAN Adapter - ELPAP11 (2.4GHz &
5GHz)
V12H005A01