DATASHEET / BROCHURE

EcoTank Business+ M3180



EcoTank Business+ M3180

يمكنك الطباعة والمسح الضوئي والنسخ وإرسال الفاكسات باستخدام هذا الطراز من EcoTank الذي يأتي مزوّدًا بكمية من الحبر تكفي لطباعة 11000 صفحة وإمكانية اتصال عبر Ethernet وWi-Fi وUSB.

{b}توفير المال{تحقق إنتاجية الحبر العالية جنبًا إلى جنب مع تقنية نفث الحبر الاقتصادية من إبسون كلاً من إجمالي منخفض لتكلفة الاقتناء وتكلفة صفحة تنافسية.{b}توفير الوقت{تعتمد هذه الطابعة الخالية من خراطيش الحبر والموثوقة الأداء على نظام محسّن لتعبئة الحبر وعبوات حبر يسهُل استخدامها، ما يُبقي تدخل المستخدم في أقل حد ممكن. ويمتاز هذا التصميم الجديد بصغر حجمه بفضل خزان الحبر الموضوع في مقدمة الطابعة والذي يحقّق رؤية واضحة لمستويات الحبر، كما يتيح وصولاً سهلاً لإعادة التعبئة. ويعني الزمن القصير لخروج الصفحة الأولى (6 ثوانٍ) من وضع السكون وسرعة الطباعة التي تبلغ 20 صفحة في الدقيقة أنك لن تنتظر مهام الطباعة لفترة طويلة. {b}توفير الطاقة{على عكس طابعات الليزر، لا تحتاج تقنية نفث الحبر إلى أي تسخين أثناء عملية الطباعة، ما يساعد على إبقاء استهلاك الطاقة في معدلات منخفضة وخفض قيمة فواتير الكهرباء.{bالميزات الملائمة للأعمال{تعني إمكانات الاتصال عبر Wi-Fi وEthernet وUSB والتصميم الذي يشغل حيزًا صغيرًا أنه يسهُل وضع الطابعة على سطح مكتب وتوصيلها بالكمبيوتر الشخصي أو الكمبيوتر المحمول الخاص بالمستخدم.

KEY FEATURES

- **انخفاض إجمالي تكلفة الاقتناء واستهلاك الطاقة**
  إبقاء تكاليف الطباعة في مستويات منخفضة جدًا
- **الإنتاجية العالية للحبر**
  طباعة عددٍ يصل إلى 11,000 صفحة باستخدام الحبر المرفق بعبوة البيع
- **توفير الوقت**
  طباعة ومسح ضوئي ونسخ وإرسال فاكسات
- **صُممت للأعمال**
  طباعة على الوجهين ودعم PCL
- **سهولة الاتصال**
  Wi-Fi وUSB وEthernet

EPSON®

EcoTank Business+ M3180

WHAT'S IN THE BOX

- الطابعة
- زجاجتان من زجاجات الحبر السائل
- وثيقة الضمان

INK COMPATIBILITY

EcoTank Pigment black ink bottle ١١٠

١١٠S EcoTank Pigment black ink bottle

٤٧٥٠-ET / ٣٧٠٠-٢٨٦٠DWF / ET-WF / ٥١٠٠-XP

Series Maintenance Box ١٥٠٠٠-ET / L٦٠٠٠ /

INK YIELD DATA

Included

Replacement

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Method	رأس الطباعة PrecisionCore™ TFP
Ink Technology	Pigment ink
Printing Resolution	x 2400 DPI 1200
PRINT	
	For detailed information on printing speeds please visit http://www.epson.eu/testing.
SCAN	
Scanner Type	مستشعر صورة الاتصال (CIS)
PAPER / MEDIA HANDLING	
Paper Formats	A4 (21.x29,7 cm), قانوني
Duplex	نعم
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm 0 (.Top, Right, Bottom, Left
Media Handling	طباعة على الوجهين تلقائيًا (A4، ورق عادي)، تغذية بالوسائط المتخصصة من الخلف
GENERAL	
Product dimensions	375 (mm x 347 mm x 346 mm (Width x Depth x Height
Noise Level	6.9 Epson Premium Glossy Photo Paper / Photo RPM mode - 56 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode B (A)
Compatible Operating Systems	Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS 10.10.x, Mac OS X 10.6.8, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012 (64bit), Windows Server 2008 R2, Windows Server 2008 (32/64bit), Windows Server 2003 R2 x64, XP Professional x64 Edition SP2, Windows XP SP3, Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10
WLAN Security	(WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES
Mobile and Cloud Printing Services	Epson Connect (iPrint), Google Cloud Print
OTHER FEATURES	
Panel	Type: Colour, Diagonal: 6.1
Memory Cards	n/a
OTHER	

LOGISTICS INFORMATION

SKU	C11CG93404BY
EAN Code	8715946655253
Country Of Origin	Philippines

1. Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712 or 29103. Quoted yields are NOT based on ISO/IEC 24711 or 29102. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set will be lower.
2. Compared to best-selling similarly-featured printers in Middle East & Africa (IDC, Quarterly Hardcopy Peripherals Tracker, Q1 2023 to Q4 2023 shipments, published Q1 2024). Comparison based on the average yield when printing. Cost per page calculated by dividing the relevant bottle/cartridge average selling price as tracked by IDC by the yield. Epson models included: Eco Tank 112 Ink Bottle Series, Eco Tank 110 Ink Bottle Series, Eco Tank 101 Ink Bottle Series, Eco Tank 103 Ink Bottle Series, Eco Tank 664 Ink Bottle Series.
3. Mobile printing solutions require a wireless and/or an Internet connection to the printer. For a list of Epson Connect enabled printers, compatible devices, apps and ways to connect, visit www.epson.com/eme
4. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.com/eme

EPSON®