EB-L695SE

DATASHEET / BROCHURE



EB-L695SE

Ідеально для професійних середовищ. Короткофокусний лазерний 3LCD-проєктор з покращенням 4K, 6000 люменів і гнучким встановленням.

KEY FEATURES

Створюючи чіткі, яскраві зображення до 4,6 мільйона пікселів, цей бюджетний лазерний проєктор ідеально підходить для великих дисплеїв у професійних просторах.

• Компактний короткофокусний дизайн для занурювального дисплея

Проєктуйте масштабовані зображення до 500” з коефіцієнтом короткофокусного проєціювання 0,5–0,7:1 та зумом 1,4x, створюючи занурювальні візуальні елементи без тіней і відблисків у компактних просторах.

• Тиха робота

Забезпечує високопродуктивний дисплей з низьким рівнем шуму 36 дБ або 26 дБ в Eco-режимі, гарантуючи тиху та зосереджену атмосферу для занурювальних візуальних вражень.

• Просте, гнучке встановлення

Фіксований центральний об’єктив із ручним зміщенням і просунутими функціями, як-от корекція фокусування по кутах, забезпечує просте налаштування й адаптивність до будь-якого середовища.

• Просунуті засоби для монтажу

Включає пакет програмних засобів та додатковий модуль зовнішньої камери для покращеної гнучкості налаштування.

PRODUCT SPECIFICATIONS

EB-L695SE

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.67 inches with C2 Fine
IMAGE	
Color Light Output	6000 Lumens - 4200 Lumens (economy)
White Light Output	6000 Lumens - 4200 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.5 - 0.7:1
Zoom	Digital, Factor: 1 - 1.4
Lens	Optical
Screen Size	100 in - 500 in
Projection Lens F Number	2
Projection Lens Focal Length	10.55 mm
Projection Lens Focus	Manual
CONNECTIVITY	
Interfaces	HDBaseT (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), USB 2.-A (2 x), Near Field Communication (NFC) (1 x), RS-232C (1 x), Jack plug out (1 x), HDMI out (1 x), USB 2. Type B (Service Only) (1 x), HDMI (HDCP 2.3) (2 x), Wireless LAN IEEE 82.11a/b/g/n/ac (Optional)
Network Protocol	SNMP, HTTPS, ESC/VP.net, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection
Other Features	21:9 aspect ratio support, 4K enhancement, A/V mute, Auto Power On, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, JPEG Viewer, Network projection, OSD copy function, PC Free, Point correction, Quick Corner, Schedule Function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, iProjection App
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT79
Projector Control	Crestron Integrated Partner, Extron XTP, AMX Device Discovery

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	362 W, 250 W (economy), 0.4 W (standby)
Product dimensions	440 mm x 368 mm x 151 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Noise Level	Normal: 36 dB (A) - Economy: 26 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Air filter, Camera module, Ceiling mount, Document camera, External Speaker, HDBaseT Transmitter, Safety wire set, Suspension adapter, Wireless LAN unit
Room Type / Application	Boardroom, Gaming, Large Meeting Room / Auditorium, Projection Mapping, Meeting room / Classroom, Signage / Retail, Sports, Visitor Attraction
Positioning	Ceiling Mounted, Desktop
Colour	Black

OTHER

EB-L695SE

WHAT'S IN THE BOX

- Main unit
- Power cable
- Remote control incl. batteries
- User manual
- Warranty document
- Quick Start Guide

OPTIONAL ACCESSORIES

- Air Filter - ELPAF65 - L6/7/89x Series
  V13H134AF0
- Cable Cover - ELPCC07B-Black - L6/7/89x Series
- Cable Cover - ELPCC07W-White - L6/7/89x Series
  V12H003AP0
- Camera Unit - ELPEC01
  V12HA46010
- Ceiling Mount - ELPMB22 - White
  V12H003B22
- Ceiling Mount - ELPMB30 - Low profile
  V12H526040
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]