

# Epson EB-X49

DATASHEET / BROCHURE



## EB-X49

**Можливість установлення майже в будь-якому місці поєднується з відмінною яскравістю й чіткістю, а також із продуктивною роботою без потреби в частому технічному обслуговуванні.**

{bЯскравий, насичений контент на великому масштабованому екрані} Насолоджуйтеся презентаціями у великому форматі з чітким, контрастним текстом, привабливим зображенням і відеоконтентом на екранах розміром до 300 дюймів. Яскравість 3600 люменів і високий коефіцієнт контрастності 16 000:1 забезпечують надзвичайну візуальну продуктивність навіть у добре освітлених приміщеннях. {bРоки конференцій без простоїв} Завдяки лампі з тривалістю експлуатації до 12 000 годин у режимі Eco. {bГнучкі можливості встановлення й розташування} Автоматична вертикальна й горизонтальна корекція кутових спотворень забезпечує гнучкість розташування проектора в приміщеннях і гарантує зображення без деформацій, а широкоформатне оптичне збільшення надає ще більше можливостей роботи. {bМережеве й бездротове з'єднання (додатково)} Підключення до мережі (за протоколом RJ45) і додаткові можливості бездротового підключення дозволяють приєднати EB-X49 до корпоративної мережі або пізніше оновити до бездротового доступу до пристроїв. {bВисокоякісний звук} У цей проектор вбудовано динамік 5 Вт, завдяки якому аудіоконтент лунає чітко й не потрібні додаткові зовнішні динаміки.

## KEY FEATURES

- **Високоякісне яскраве зображення**

Технологія 3LCD й однаково високі яскравість білого кольору та колірної яскравість

- **Портативність**

Невеликі розмір і вага дозволяють легко переносити проектор і користуватися ним у різних приміщеннях

- **Широкий вибір варіантів підключення**

Можливості мережевого й бездротового зв'язку

- **Низька загальна вартість володіння**

До 12 000 годин експлуатації лампи в режимі Eco

- **Універсальне й гнучке керування**

Відтворення зображення з різних джерел через HDMI і додаткові можливості бездротового підключення

**EPSON®**

## PRODUCT SPECIFICATIONS

Epson EB-X49

### TECHNOLOGY

Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.55 inches with C2 Fine

### IMAGE

Color Light Output	3600 Lumens - 2400 Lumens (economy)
Resolution	XGA
Light Source	Lamp
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours

### OPTICAL

Throw Ratio	1.48 - 1.77:1
Lens	Optical
Screen Size	30 in - 300 in
Projection Lens F Number	1.72
Projection Lens Focal Length	20.28 mm
Offset	8 : 1

### CONNECTIVITY

Interfaces	Wireless LAN IEEE 802.11a/b/g/n/ac (Optional), Ethernet interface (1 Base-TX / 1 Base-T) (1 x), USB 2.0 (1 x), Composite in (1 x), USB 2.0-A (1 x), Jack plug in (2 x), HDMI in (1 x), Jack plug out (1 x), RS-232C (1 x), Cinch audio out (1 x), VGA out (1 x), VGA in (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink

### ADVANCED FEATURES

Security	Kensington lock, Security cable hole, Wireless LAN unit lock
Other Features	AV Mute Slide, Automatic keystone correction, Built-in speaker, Digital zoom, Direct Power on/off, Document Camera Compatible, Easy OSD pre-setting, Horizontal and vertical keystone correction, Network projection, OSD copy function, PC Free, Quick Corner, Split-Screen-Function, iProjection set-up by QR code, iProjection set-up by NFC, iProjection App, CEC compatible
Video Colour Modes	Blackboard, Dynamic, Presentation, Theatre, sRGB
Projector Control	AMX, Control4, Crestron, Extron

## PRODUCT SPECIFICATIONS

### GENERAL

Power consumption	286 W, 327 W (economy), 180 W (standby)
Product dimensions	302 mm x 249 mm x 87 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection, Epson Projector Management
Noise Level	Normal: 37 dB (A) - Economy: 28 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wireless transmitter - ELPWT1
Loudspeaker	5 W
Positioning	Ceiling Mounted, Desktop
Colour	White

### OTHER

## Epson EB-X49

### WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Main unit
- HDMI Cable
- Quick Start Guide
- User Guide Kit (CD)
- Warranty document

### OPTIONAL ACCESSORIES

- Air Filter - ELPAF32 - EB-SXW11/12/14  
V13H134A32
- Ceiling Mount - ELPMB23 - White  
V12H003B23
- Ceiling pipe - ELFPF13 - 668-918mm  
V12H003P13
- Ceiling pipe - ELFPF14 - 918-1168mm  
V12H003P14
- External Speaker - ELPSP02  
V12H467040
- External Speaker - ELPSP02 - [240v]
  
- Lamp – ELPLP97 – EB9XX/W49/X/E20/U50/  
EB-x05/x41/x42/EH-TW6  
V13H010L97
- Safety Wire - ELPWR01  
V12H003W01
- Soft Carry Case - ELPKS70  
V12H001K70
- Wireless LAN Adapter - ELPAP11 (2.4GHz &  
5GHz)  
V12H005A01