Epson EB-L265F

DATASHEET / BROCHURE



EB-L265F

Best for professional environments. 4,600-lumen Full HD 3LCD projector for versatile business and education use.

Innovative and cost effectiveEpson's advanced laser technology is bright, robust and reliable for a flexible and easy to use digital signage solution. It offers bright and vivid colours in a cost-effective solution capable of creating large displays or even projecting onto 3D objects.Flexible display optionsThe EB-L265F enables scalable display sizes of up to 310 inches with a single projector - even larger when edge-blending 2 units. Full HD, 4,600 lumen brightness and 3LCD technology offer bright colours and high quality - perfect for creating engaging and informative displays, even in bright spaces. It can be mounted wherever needed - wall, floor or ceiling (inc.on a lighting track) with optional accessories. A white model is also available (EB-L260F) to ensure the projector is as discrete as possible.Create dynamic contentEpson offers free apps for content creation (Epson Creative Projection & Epson Projector Content Management). Content can be played directly from USB (including playlists, videos, and signage content) using the built-in playback feature. Users can even upload and playback content wirelessly with built-in Wi-Fi and Miracast functionality.Low maintenance and high reliabilityUp to 20,000 hours maintenance-free use using a laser light source with a 5 year warranty make this a cost-effective fit-and-forget display solution you can rely on.

KEY FEATURES

- **Experiential signage solution**
  Large, bright display for signage, or project onto 3D objects
- **Up to 310-inch display**
  Full HD resolution, 4,600 lumen brightness and 3LCD technology
- **Installation flexibility**
  Wall, ceiling, floor, or lighting track, with 360 degree rotation
- **Cost effective**
  20,000 hours maintenance free - 5 year warranty
- **Flexible playback**
  Play content directly from USB stick or Miracast

PRODUCT SPECIFICATIONS

Epson EB-L265F

TECHNOLOGY	
Projection System	3LCD Technology RGB liquid crystal shutter
LCD Panel	0.62 inches with C2 Fine
IMAGE	
Color Light Output	4600 Lumens - 3200 Lumens (economy)
White Light Output	4600 Lumens - 3200 Lumens (economy)
Resolution	1080p
High Definition	Full HD
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 30
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.32 - 2.12:1
Zoom	Digital, Factor: 1 - 1.62
Lens	Optical
Screen Size	31 in - 310 in
Projection Lens F Number	1.77
Projection Lens Focal Length	29.1 mm
Projection Lens Focus	Manual
Offset	10 : 1
CONNECTIVITY	
Interfaces	Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), Composite in (1 x), RS-232C (1 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), USB 2.0-A (1 x), VGA out (1 x), Jack plug in (2 x), USB 2.0 Type B (Service Only) (1 x), Jack plug out (1 x), Miracast (1 x), VGA in (2 x), HDMI (HDCP 2.3) (2 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, PJLink, IPv6, SNMP, ESC/VP.net
ADVANCED FEATURES	
Security	Kensington lock, Security bar, Control panel lock, Padlock, Security cable hole, Wireless LAN unit lock, Password protection, Wireless LAN security
Other Features	A/V mute, Arc Correction, Auto Power On, Auto source search, Automatic keystone correction, Built-in speaker, Customizable user logo, Direct Power on/off, Document Camera Compatible, Edge Blending, Home Screen, Horizontal and vertical keystone correction, Long light source life, OSD copy function, Quick Corner, Schedule Function, Screen Mirroring, Split-Screen-Function, Super resolution, Web Remote, Web Control, Wireless LAN capable, iProjection App, PC Free, CEC compatible
Video Colour Modes	Dynamic, Cinema, sRGB, Multi Projection, Presentation, Blackboard
Projector Control	AMX Device Discovery, Control4 Simple Device Discovery Protocol, Extron IP Link, Crestron RoomView, Crestron Integrated Partner

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Power consumption	199 W, 144 W (economy), 0.5 W (standby)
Heat Dissipation	884 BTUperhour
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager, Epson Projector Management
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wireless transmitter - ELPWT01
Loudspeaker	16 W
Room Type / Application	Signage / Retail, Visitor Attraction, Projection Mapping
Positioning	Floor, Ceiling Mounted, Lighting Track, Wall Mounted, Desktop
Colour	Black

OTHER

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Warranty document
- User guide
- HDMI Cable
- Main unit

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series
  V13H134A60
- Ceiling mount / Floor stand - ELPMB60B
  V12H963110
- Ceiling pipe - ELPFP13 - 668-918mm
  V12H003P13
- Ceiling pipe - ELPFP14 - 918-1168mm
  V12H003P14
- Control and Connection Box - ELPCB03

- Control and Connection Box - ELPCB03 [240v]
  V12H927040DA
- Control and Connection Box - ELPCB03N
  V12HB11040DA
- External Speaker - ELPSP02
  V12H467040
- External Speaker - ELPSP02 - [240v]
  V12H467040DA
- Lighting Track Mount - ELPMB61B
  V12H964140

EPSON®