

Epson L6490 MEAF



EcoTank Business+ L6490F

Best for demanding businesses that need ultra-fast colour 4-in-1 performance with high-capacity ink.

Get more done in less time.

Take your business printing to the next level with this ultra-fast and efficient printer that can deliver a first page in as little as 7 seconds¹. Multifunction A4 EcoTank.

Print, copy, scan and fax with the L6490 which features double-sided printing, a 250-sheet front paper tray and 35-page automatic document feeder. It's easy to navigate the extensive range of features with the 6.1cm LCD touch-screen.

Keep on saving.

Making a saving every time you print with this EcoTank that delivers an incredibly low cost-per-page. Unlike other printers, EcoTank features large ink tanks that you fill with low-cost ink bottles.

Business-quality printing.

The fast drying EcoTank 112 ink series features all pigment inks for smudge, water and highlighter resistant prints. You can produce up to 13,300 pages in black and 5,200 in colour with the included ink^{**}.

Print from almost anywhere.

With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint and Smart Panel apps³. Easy to use and reliable.

Filling the ink tanks is simple with the resealable, intuitive and mess-free ink bottles. Epson's unique Heat-Free PrecisionCore Technology offers improved reliability, reduced downtime and less environmental impact. No warm up time means the first page prints fast uses less power.

KEY FEATURES

- **Ultra-fast print speeds**
Up to 17ipm^{****}
- **Ultra-low-cost per page**
Economical ink tank system
- **Easy to use front ink tank**
Enjoy hassle-free refills with enhanced ink bottles
- **Mobile printing and connectivity**
Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps^{***}
- **Designed for business**
A4 multifunction printer, 250-sheet front tray, 35-sheet ADF

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ Print Head
Minimum Droplet Size	3.3 pl, With Variable-Sized Droplet Technology
Ink Technology	Pigment ink
Printing Resolution	4800 x 1200 DPI

PRINT

Printing Speed ISO/IEC 24734	17 Pages/min Monochrome, 9.5 Pages/min Colour
------------------------------	---

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

SCAN

Scanner Type	Contact image sensor (CIS)
--------------	----------------------------

PAPER / MEDIA HANDLING

Paper Formats	User defined
Duplex	Yes
Print Margin	0 mm top, 0 mm right, 0 mm bottom, 0 mm left (Wherever margin is defined. Otherwise 3mm Top, Right, Bottom, Left.)
Media Handling	Automatic duplex (A4, plain paper)

GENERAL

Product dimensions	346 mm x 375 mm x 347 mm (Width x Depth x Height)
Noise Level	5.1 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 38 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode
Compatible Operating Systems	Windows 8.1, Windows 8, Mac OS X 10.6.8 or later, Windows 7, Windows Vista, Windows XP, XP Professional x64 Edition, Windows 10
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES)
Mobile and Cloud Printing Services	Apple AirPrint, Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud)

OTHER FEATURES

Panel	Type: Colour, Diagonal: 610
Features	Touchscreen

OTHER

LOGISTICS INFORMATION

Epson L6490 MEAF

WHAT'S IN THE BOX

- Warranty document
- Main unit
- Power cable
- Setup guide
- 1 set of ink (1x 127ml BK, 3x 70ml cmY) + Extra Black
- Driver and utilities (CD)

INK COMPATIBILITY

- 112 EcoTank Pigment Black ink bottle
- 112 EcoTank Pigment Cyan ink bottle
- 112 EcoTank Pigment Magenta ink bottle
- 112 EcoTank Pigment Yellow ink bottle

INK YIELD DATA

Included	* 13,300 Pages	* 5,200 Pages
----------	----------------	---------------

Replacement

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower.

. Drying times depends also on humidity, temperature and other conditions. Do not touch the printed side until ink is completely dry. Moisture and oils from your skin can also affect print quality. Even after dry, avoid rubbing or scratching the surface of the printed paper. For Photo printing, Matte Photo paper is recommended.

EPSON®