

Epson EB-1481Fi

DATASHEET / BROCHURE



EB-1481Fi

Best for professional environments. Versatile 3LCD projector for business and education use.

The intuitive and easy-to-use UI, new touch home screen and new interactive OSD menu make it simple to set up and navigate across functions. Featuring multi-touch pen and finger capabilities, wireless BYOD connectivity and screen mirroring (Miracast) and optional wall mount. It also has secure user collaboration tools and an array of powerful connectivity options, both wireless and wired. The Epson iProjection App is available to download for free, providing seamless wireless connectivity and collaboration control from multiple devices and platforms. It's compatible with Windows, Office 365 suite and iOS, allowing the use of Office applications via PCs and tablets. Combine up to four video sources in one display, such as video conference systems and presentations, to optimise meeting interactions. Once installed, use for up to 20,000 hours without any maintenance, with the additional peace of mind of a five-year warranty.

KEY FEATURES

- **Flexible display options and sizes**
Cater for any working environment based user needs
- **All-in-one interactive meeting display**
Combines multiple resources in one interactive collaboration device
- **Increase productivity & agile working**
Share and display content from a range of devices simultaneously
- **Sliding split screen**
Up to four displays in one image - project images from different sources
- **Easy installation**
Quick set-up with auto-adjusting calibration function

EPSON®

PRODUCT SPECIFICATIONS

Epson EB-1481Fi

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	0.62 inches with C2 Fine
IMAGE	
Color Light Output	5000 Lumens - 3500 Lumens (economy)
White Light Output	5000 Lumens - 3500 Lumens (economy)
Resolution	1080p
Contrast Ratio	2,500,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 3, Manual horizontal: 3
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.27 - 0.37:1
Zoom	Digital, Factor: 1 - 1.35
Lens	Optical
Screen Size	65 in - 100 in
Projection Distance Wide	0.4 m (65 inch screen)
Projection Distance Tele	0.6 m (100)
Projection Lens F Number	1.5
Projection Lens Focal Length	3.9 mm
Projection Lens Focus	Manual
Offset	9 : 1
CONNECTIVITY	
Interfaces	Finger-touch interface (1 x), HDMI out (1 x), Sync. out (1 x), Component in (1 x), USB 2.0 (2 x), Jack plug out (1 x), Wireless LAN IEEE 802.11a/b/g/n/ac (1 x), RS-232C (1 x), Wi-Fi Direct (1 x), Sync. in (1 x), Multi-Touch interface (1 x), Microphone input (1 x), USB 2.0-A (2 x), Ethernet interface (100 Base-TX / 10 Base-T) (1 x), VGA in (2 x), Jack plug in (3 x), Powered USB (1 x), VGA out (1 x), Miracast (1 x), HDMI in (3 x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	PJLink, SNMP, IPv6, IPv4, HTTPS, ESC/VP.net
ADVANCED FEATURES	
Security	Kensington lock, Password protection, Padlock, Wireless LAN security, Control panel lock, Password lock
Other Features	Auto Power On, Auto Calibration, Built-in speaker, Customizable user logo, Digital zoom, Direct Power on/off, Dual Pen Support, Email notification, Finger-touch support, Freeze image, Instant on/off, Interactive, Microphone input, OSD copy function, PC Interactive, iProjection App, Easy OSD pre-setting, Network administration, Quick Corner, Sliding split-screen feature, Super resolution, Wireless LAN capable, iProjecton set-up by QR code, CEC compatible, Interactive OSD menu, Document Camera Compatible, Driverless installation, Split-Screen-Function, Screen share, Set-up wizard, Screen Mirroring, Fit to Screen, Image Shift, Arc Correction, Schedule Function, Web Control, Web Remote, Projection App for Chromebook, PC free annotation, Mail notification function, Whiteboard sharing function
Video Colour Modes	Blackboard, Dynamic, Cinema, Presentation, sRGB, DICOM SIM
Projector Control	AMX, Crestron, Extron, Crestron (RS-232c only), Crestron Integrated Partner, Crestron RoomView, Extron IP Link, Extron XTP, AMX Device Discovery, Control4 Simple Device Discovery Protocol

EPSON[®]

PRODUCT SPECIFICATIONS

GENERAL	
Heat Dissipation	1,244 BTUperhour
Product dimensions	458 mm x 375 mm x 209.5 mm (Width x Depth x Height)
Supply Voltage	AC 220 V - 240 V, 50 Hz - 60 Hz
Compatible Operating Systems	Windows 10 (32/64 bit)
Included Software	Easy Interactive Tools, Epson Projector Management, EasyMP Multi PC Projection
Noise Level	Normal: 36 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Options	Pen tip(Felt), Pen tip(Teflon), External Speaker, Document camera, Wireless LAN unit, Air filter ELPAF38
Loudspeaker	16 W
Room Type / Application	Boardroom, Meeting room / Classroom
Positioning	Wall Mounted
Colour	White

OTHER

Epson EB-1481Fi

WHAT'S IN THE BOX

- Interactive pens
- Power cable
- Remote control incl. batteries
- Replacement pen tips
- Pen Holder/Stand
- Cable cover
- 2 x Pen tip(Teflon)
- Lens cap
- 4 x Pen tip(Felt)
- USB cable
- Quick Start Guide
- Safety Cable
- Finger touch unit

OPTIONAL ACCESSORIES

- Air Filter - ELPAF56 - L600/EB-14XX Series
V13H134A56
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx
V12HA06A06
- ELPMB63 - Finger Touch Wall Bracket for
ELPFT01
V12HA05A09
- External Speaker - ELPSP02
V12H467040
- External Speaker - ELPSP02 - [240v]
V12H467040DA
- Interactive Pen - ELPPN05A - Orange -
EB-6xxWi/Ui / 14xxUi
V12H773010
- Interactive Pen - ELPPN05B - Blue - EB-6xx-
Wi/Ui / 14xxUi
V12H774010
- Replacement Hard Pen Tip - ELPPS03 (6pcs)
V12H775010
- Replacement Soft Pen Tip - ELPPS04 (12pcs)
V12H776010
- Safety Wire - ELPWR01
V12H003W01