EB-PU2116W

DATASHEET / BROCHURE





EB-PU2116W

Ідеально для інсталяцій у залах середнього та великого розміру. Компактний лазерний 3LCD-проєктор WUXGA з яскравістю 16 000 люменів, покращенням 4K і сертифікатом IP5X.

Зменшена вага та розмір означають, що проєктор простіше зберігати, транспортувати та встановлювати, заощаджуючи на складських площах, а також на витратах на робочу силу та доставку. Цей 3LCD-проєктор з високою яскравістю в люменах пропонує роздільну здатність WUXGA з покращенням 4K і HDR для насиченої текстури та чіткіших зображень. Функціональність EB-PU2116W забезпечує просте встановлення, складання, гнучкість об'єктивів і керування. Він включає вбудовану обробку для складання без ПК, що означає, що два сумісні проєктори можна скласти для подвоєння яскравості без потреби в зовнішньому обладнанні. Має видатну пилостійкість, оскільки герметично закритий оптичний механізм і блок лазерного джерела світла забезпечують стабільну яскравість на виході протягом тривалих періодів, навіть у середовищах із високою запиленістю.

KEY FEATURES

- **Ультралегкий і компактний**

  Простий у зберіганні, транспортуванні та встановленні
- **Вражаюче проєціювання зображення**

  16 000 лм, технологія покращення 4K, роздільна здатність WUXGA
- **Простий у використанні**

  Просте встановлення, складання, гнучкість об'єктивів і керування
- **Надійність «встановив і забув»**

  Удосконалена пилостійка конструкція — сертифікат IP5X
- **Екологічні переваги**

  Менше споживання енергії, менша упаковка, менша вага

EPSON®

PRODUCT SPECIFICATIONS

EB-PU2116W

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	1.03 inches with C2 Fine
IMAGE	
Color Light Output	16000 Lumens - 11200 Lumens (economy)
White Light Output	16000 Lumens - 11200 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	5,000,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Colour Video Processing	10 Bits Color
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	0.35 - 7.41:1
Zoom	Digital, Factor: 1 - 1.6
Screen Size	60 in - 1000 in
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	Ethernet Interface (1 Base-T/ 1-Base TX/ 1-Base-T) (1 x), Remote (1 x), Wireless LAN IEEE 82.11a/b/g/n (Optional), USB content playback (1 x), USB 2. Type B (Service Only) (1 x), Near Field Communication (NFC) (1 x), USB 2.-A (2 x), HDBaseT (1 x), HDMI in (1 x), Jack plug out (1 x), RS-232C (1 x), DVI in (1 x), VGA in (1 x)
Network Protocol	IPv6, ESC/VP.net, PJLink, HTTPS, SNMP
ADVANCED FEATURES	
Security	Kensington lock, Security bar, Password lock, Password protection, Wireless LAN unit lock, Wireless LAN security
Other Features	4K enhancement, A/V mute, Auto Power On, Auto source search, Direct Power on/off, Edge Blending, Lens position memory, Long light source life, OSD copy function, Power on button, Quick Corner, Schedule Function, Split-Screen-Function, Super resolution, Web Control, Web Remote, iProjection App, 21:9 aspect ratio support, Point correction, Freeze image, Horizontal and vertical keystone correction
Video Colour Modes	Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection, BT79
Projector Control	AMX, Crestron, Extron

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Product dimensions	586 mm x 492 mm x 218 mm (Width x Depth x Height)
Heat Dissipation	3,682 BTUperhour
Supply Voltage	AC 200 V - 240 V, 50 Hz - 60 Hz
Included Software	Epson Projector Content Manager, Epson Projector Management, Epson Projector Professional Tool, Epson Creative Projection, Epson Projector Config Tool
Noise Level	Normal: 38 dB (A) - Economy: 34 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Ceiling mount, Wireless LAN unit, Camera module
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Meeting room / Classroom, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Desktop, Flying Frame
Colour	White

OTHER

WHAT'S IN THE BOX

- Power cable
- Remote control incl. batteries
- Cable cover
- Lens connector cap
- Document Pack
- Initial toner cartridges
- Main unit
- Quick Start Guide

OPTIONAL ACCESSORIES

- Camera Unit - ELPEC01
  V12HA46010
- Ceiling Mount - ELPMB68
  V12H006AE0
- Extension Pole - ELPMB70 - For ELPMB68
  V12H006AG0
- Lens - ELPLL08 - Long throw - EB-PU Series
  V12H004L08
- Lens - ELPLM10 - Mid throw 3 - EB-PU Series
  V12H004M0A
- Lens - ELPLM11 - Mid throw 4 - EB-PU Series
  V12H004M0B
- Lens - ELPLM15 - Mid throw - EB-PU Series
  V12H004M0F
- Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
  V12H004UA3
- Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series
  V12H004U04
- Lens - ELPLW06 - Wide zoom 2 - EB-PU Series
  V12H004W06

EPSON®