



Epson EB-760WI



KEY FEATURES

Interactive HD display for any room

UST display for unrestricted 73-100" viewing (no shadows/reflections)

Bright and energy efficient laser

4,100lm CLO with 3LCD technology for brighter colours at only 205W

Effortless connectivity options

Auto-on, wired / wireless display with USB 2A output for smart sticks

Simple to use and built to last

Virtually maintenance free with 5-year, 12,000hr warranty

Document camera compatibility

Create and record a live, totally immersive lesson or presentation

EB-760WI

Best for collaborative workspaces and classrooms. Ultra-short-throw interactive laser display with 4,100 lumens

The EB-760Wi is a step up from the EB-760W, with added interactive features. Interactive technology enables two digital pens to be used simultaneously on the display (finger touch available through optional accessory FT01).

Presentations can be controlled and brought to life with on-screen annotations, while a variety of convenient built-in tools support productivity. An optional Epson visualiser camera can be controlled via the display, projecting documents or objects from a desk for everyone to see in incredible HD detail. The ultra short throw lens allows safe, discreet positioning above the display, enabling presenters free access to interact without casting shadows. With a 4,100 lumens laser-light source, combined with 3LCD technology, it produces a large, bright and vibrant display up to 100", visibly clear from all angles and at a distance. Versatile wired and wireless connectivity options, including screen mirroring via Miracast™, allow participants to effortlessly share content from their PCs or mobile devices. Unlike a flat-panel display, there is no heavy, breakable, glass panel to create disruptive, reflected blind spots from certain angles, and presenters are not subjected to LCD panel direct blue light radiation, believed to damage eyes.

TECHNOLOGY	
تقنية 3LCD عطاء عدسة الكريستال السائل من RGB	Projection System
inches with C2 Fine 0.59	LCD Panel

IMAGE	
Color Light Output	Lumens - 2800 Lumens (economy) 4100
White Light Output	Lumens - 2800 Lumens (economy) 4100
Resolution	WXGA
High Definition	HD ready
Contrast Ratio	5,000,000
Light Source	الليزر
Laser Light source	hr Durability High, 30000 hr Durability Eco 20000
Keystone Correction	Manual vertical: 3, Manual horizontal: 3
Colour Video Processing	Bits Color 10
Colour Reproduction	Upto 1.07 billion colours

OPTICAL	
0.37:1 - 0.27	Throw Ratio
Digital, Factor: 1 - 1.35	Zoom
بصري	Lens
in - 100 in 53	Screen Size
1.6	Projection Lens F Number
mm 3.7	Projection Lens Focal Length
Manual	Projection Lens Focus
1 : 6	Offset

CONNECTIVITY	
1) Ethernet واجهة توصيل 1) Ethernet, Composite (1 x) مدخل, A (2 x) من الفئة 2, USB 2 منفذ, VGA (1 x), Miracast (1 x) مدخل, Base-TX/1 Base-T (1 x) شبكة محلية لاسلكية (2) USB, (1 x) WiFi 5 (1 x), LAN IEEE 802.11a/b/g/n/ac. النوع B (الخدمة فقط) (2 x) مدخل ميكروفون (1 x), مدخل (2 x) VGA, (3 x) HDMI, مدخل صوت بمقبس استريو صغير (3 x), RS-232C (1 x), توجيه (1 x) Wi-Fi, مخرج صوت بمقبس استريو صغير (1 x)	Interfaces
بنية تحتية/مخصصة لأغراض معينة	Epson iProjection App
IPv6, PjLink, ESC/VP.net, SNMP, HTTPS, IPv4	Network Protocol

ADVANCED FEATURES	
حماية كينسينغتون, Padlock, فتحة كابل الحماية, قفل وحدة LAN لاسلكية, حماية كلمة المرور, أمان شبكة LAN لاسلكية, إغلاق لوحة التحكم, حماية كلمة المرور	Security
AV mute, تصحيح محاذاة الانحناء, تشغيل تلقائي, البحث التلقائي عن المصدر, سماعات مدمجة, شعار المستخدم القابل للتخصيص, زوم رقمي, التشغيل/إيقاف التشغيل المباشر, كاميرا الوثائق المتوافقة, Email notification, تصحيح انحراف أفقي ورأسي, إزاحة الصورة, متصفح JPEG, عد طو با, لمصدر الضوء, طابعة النسخ المعبأة مسبقاً, شاشة على الشاشة, عرض ضوء, عد الشبكة بدء, كمنبه Power	Other Features

WHAT'S IN THE BOX

- كابل للكهرباء
- التحكم عن بعد مع بطاريات
- أقلام تفاعلية
- 2 x رأس قلم (تفلون)
- 4 x رأس قلم (لباد)
- حامل/قاعدة القلم
- دليل التشغيل السريع
- كابل USB
- Projector feet
- وثيقة الضمان
- Corner markers for auto screen adjustment

OPTIONAL ACCESSORIES

- Air Filter - ELPAF60 - EB-7XX / EB-L2xx Series •
V13H134A60
- Ceiling pipe - ELPPFP13 - 668-918mm •
V12H003P13
- Ceiling pipe - ELPPFP14 - 918-1168mm •
V12H003P14
- Control and Connection Box - ELPCB03 •
V12H927040
- Control and Connection Box - ELPCB03 [240v] •
- Control and Connection Box - ELPCB03N •
V12HB11040DA
- ELPFT01 - Finger Touch Unit •
V12H007A24
- Wall Mount - ELPMB62 - EB-7xx / EB-8xx •
V12HA06A06
- ELPMB63 - Finger Touch Wall Bracket for •
ELPFT01
V12HA05A09
- External Speaker - ELPSP02 •
V12H467040

Wireless Presentation Systems

GENERAL	
Power consumption	W, 263 W (economy), 141 W (standby) 197
Product dimensions	mm x 395 mm x 133 mm (Width x Depth x Height) 356
	V11HA80080 SKU
Supply Voltage	8715946715261 AC 100 V - 240 V, 50 Hz
	Philippines Country Of Origin
Noise Level	Normal: 37 dB (A) - Economy: 27 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	% Operation 20 % - 80 %, Storage 10 % - 90
Options	رأس قلم(تفلون)
Loudspeaker	W 16
Room Type / Application	غرفة اجتماعات / قاعة دراسية
Positioning	تركيب في السقف، سطح المكتب، تركيب على الحائط
Colour	White

OTHER