EB-L1755U

DATASHEET / BROCHURE



EB-L1755U

Ідеально для великих залів і аудиторій. Лазерний 3LCD-проєктор WUXGA з яскравістю 15 000 люменів, технологією покращення 4K і встановленням під кутом 360°.

Зробіть свої презентації, зображення та відео виразними завдяки яскравому та чіткому проєціюванню цього лазерного 3LCD-проєктора. Розроблений для великих залів, він забезпечує насичені, яскраві зображення з високою роздільною здатністю WUXGA навіть при денному світлі, а технологія неорганічного фосфорного колеса гарантує підвищену стійкість до світла та тепла, забезпечуючи виняткову надійність протягом до 83 000 годин[1]. Для перегляду найвищого рівня проєктор оснащено унікальною технологією покращення 4K, яка надає зображенням виняткової чіткості та ясності й забезпечує добру розбірливість тексту в презентаціях. Завдяки широкому асортименту моторизованих об'єктивів, зокрема опціональному ультракороткофокусному (UST) об'єктиву, проєктор отримує справжню гнучкість встановлення під кутом 360°, що дає змогу розмістити його практично будь-де — без втрати яскравості або спотворення зображення. Проєктор також обладнано вбудованою камерою для точного калібрування та зйомки діагностичних зображень (її можна повністю вимкнути для запобігання віддаленому доступу). Усі моделі серії EB-L1000 можуть використовувати безкоштовне програмне забезпечення Epson Professional Projector Tool, доступне з грудня 2017 року. Воно дає змогу швидко та просто налаштовувати інсталяції з кількох проєкторів, а також застосовувати передові техніки, такі як проєкційне картування та зрощення країв.

KEY FEATURES

- **Технологія лазерного джерела світла**

  Виняткова яскравість і кольори з надійністю «встановив і забув»

- **HD-зображення з покращенням 4K**

  Винятково чітке, ясне зображення та детально розбірливий текст

- **Універсальне нове програмне забезпечення**

  Налаштування інсталяцій із кількох проєкторів і використання передових технік проєціювання

- **Гнучке встановлення під кутом 360°**

  Справжня гнучкість без спотворень і втрати яскравості

- **Забезпечення спокою і впевненості**

  Продукт поставляється з гарантією на 5 років (або 20 000 годин).

PRODUCT SPECIFICATIONS

EB-L1755U

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	1.03 inches with C2 Fine
IMAGE	
Color Light Output	15000 Lumens - 10500 Lumens (economy)
White Light Output	15000 Lumens - 10500 Lumens (economy)
Resolution	WUXGA
High Definition	4K enhancement
Contrast Ratio	2,500,000
Light Source	Laser
Laser Light source	20000 hr Durability High, 30000 hr Durability Eco
Keystone Correction	Manual vertical: 30, Manual horizontal: 45
Colour Reproduction	Upto 1.07 billion colours
OPTICAL	
Throw Ratio	1.57 - 2.56:1
Zoom	Digital, Factor: 1 - 1.6
Lens	Optical
Screen Size	60 in - 500 in
Projection Lens F Number	2.5
Projection Lens Focal Length	57.35 mm
Projection Lens Focus	Motorized
CONNECTIVITY	
Interfaces	HD-SDI (1 x), RS-232C (1 x), USB 2. Type B (Service Only) (1 x), VGA in (1 x), VGA out (1 x), Jack plug out (1 x), Wireless LAN b/g/g 25GHz (Optional), BNC in (1 x), Jack plug in (3 x), HDBaseT (1 x), HDMI in (1 x), DVI in (1 x), Ethernet interface (1 Base-TX / 1 Base-T) (1 x)
Epson iProjection App	Ad-Hoc / Infrastructure
ADVANCED FEATURES	
Security	Password protection, Wireless LAN security, Wireless LAN unit lock, Security bar, Kensington lock
Other Features	Lens position memory, Frame interpolation, Customizable user logo, Auto Calibration, Absolute Black, 4K enhancement, Integrated camera for image calibration & image capture
Video Colour Modes	Multi Projection, DICOM SIM, Presentation, Dynamic, Cinema, BT79
Projector Control	Crestron, AMX, Extron

EPSON®

PRODUCT SPECIFICATIONS

GENERAL	
Product dimensions	586 mm x 492 mm x 211 mm (Width x Depth x Height)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Included Software	EasyMP Multi PC Projection, EasyMP Monitor
Noise Level	Normal: 40 dB (A) - Economy: 32 dB (A)
Supported Temperature	Storage -10 °C - 60 °C
Supported Humidity	Operation 20 % - 80 %, Storage 10 % - 90 %
Options	Wireless LAN unit, Quick wireless USB key, HDBaseT Transmitter
Room Type / Application	Boardroom, Large Meeting Room / Auditorium, Projection Mapping, Rental / Staging, Signage / Retail, Visitor Attraction
Positioning	Ceiling Mounted, Flying Frame
Colour	Black

OTHER

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Computer cable
- Cable cover
- CD Manual

OPTIONAL ACCESSORIES

- Air Filter - ELPAF51 - EB-L1000 series
  V13H134A51
- Ceiling Mount - ELPMB68
  V12H006AE0
- Extension Pole - ELPMB70 - For ELPMB68
  V12H006AG0
- Lens - ELPLL08 - Long throw - EB-PU Series
  V12H004L08
- Lens - ELPLM10 - Mid throw 3 - EB-PU Series
  V12H004M0A
- Lens - ELPLM11 - Mid throw 4 - EB-PU Series
  V12H004M0B
- Lens - ELPLM15 - Mid throw - EB-PU Series
  V12H004M0F
- Lens - ELPLU03S - Short throw off axis 1 - EB-PU Series
  V12H004UA3
- Lens - ELPLU04 - Short throw off axis 2 - EB-PU Series
  V12H004U04
- Lens - ELPLW05 - Wide zoom 1 - EB-PU Series
  V12H004W05

EPSON®